

LPC-490 - POWERFUL MINI PC WITH MULTI GIGABIT LAN



\$1,060.00 USD

Featuring a high performance Small PC with abundant network connectivity

- Powerful 8th Generation Intel® Celeron®, Pentium®, and Core™ Processors
 - 10-48 VDC Operation, ideal for mobile/field
 - Includes 3-Pin locking power connector and mobile hardware start-up and shutdown features
 - Built-in 4 Gigabit LAN, 4 USB 3.0, Audio, Serial, Video
 - Low Profile Rugged Aluminum Chassis
 - Slim Slot Loading Optical Drives
 - Solid State Hard Drives (SSD) optional
 - Windows 10, Windows 10 IoT, Server 2019, and Linux Compatible
 - RoHS, CE & FCC certified





GALLERY IMAGES







PRODUCT DESCRIPTION

The LPC-490 is a high performance Mini PC featuring a multitude of I/O, which includes 4 RJ45 Gigabit LAN ports, as well as a DVI-I, and DisplayPort video ports. It is offered with a range of Intel® Coffee Lake 8th Generation Processors up to Core™ i7. All this power is packed into one tiny machine that is small enough to fit on the palm of your hand!

The LPC-490 Little PC is packed with features including a wide DC input range of 10-48V, a locking 3-Pin Power Jack, voltage power on sense (ideal for mobile applications), up to 3 Drives in a combination of M.2 NVMe[™], 2.5" Hard Drives or Solid State Drives with optional onboard Raid support, an optional front slot loading Optical Drive or removable drive, up to 64GB memory, onboard audio, and much more.

Typical applications include:

- Instrumentation and Control
 - Security
 - Mobile & Vehicle PC
 - VPN
 - Network Appliance
 - Kiosk
 - Data acquisition
 - IoT (Internet of Things)
 - Mini Servers

The LPC-490 series adds to Stealth's robust lineup of Small Form Factor Mini PCs designed to fit in space-confined areas and are ideal for demanding applications within the Industrial, Commercial, Military & Defense, Scientific Research, Public Safety, Utility, Transportation, Mining and Telecommunications markets.



ADDITIONAL INFORMATION

Intel® Celeron® G4900T (2 Cores / 2 Threads, 2.9Ghz)

Intel® Pentium® Gold G5400T (2 Cores / 4 Threads, up to 3.1Ghz)

Intel® Core™ i3-8100T (4 Cores / 4 Threads, 3.10Ghz) **Processor**

Intel® Core[™] i5-8500T (6 Cores / 6 Threads, up to 3.5Ghz)

Intel® Core™ i7-8700T (6 Cores / 12 Threads, up to 4.00Ghz)

Chipset Intel® Q370 Chipset (Coffee Lake)

2x DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory Memory

Optional Onboard RAID configurations (0, 1), requires multiple

drives

Internal Storage SATA III (6Gb/s and 3Gb/s) support

Optional Solid State Disk Drive (SSD)

(1) M.2 E-key, 2230 **Internal Expansion Option**

Optical Drives

Networking

(1) M.2 M-key, 2280

Optional 2.5" Removable Drive Bay

Optional Slim Slot Loading DVD-RW / CD-RW (SATA)

Optional DVD-RW / Blu-Ray Burner Serial ATA (SATA)

Intel® HD Graphics 610 (Intel® Celeron and Pentium Processors) Video

Intel® HD Graphics 630 (Intel® 8th and 9th Generation Processors)

Includes DVI-I & DisplayPort video ports

(1) Integrated 10/100/1000 Base-T Intel® i219LM

(3) Integrated 10/100/1000 Base-T Intel® i211AT

Optional 801.11a/b/g/n/ac Dual Band (2.4GHz and 5GHz) +

Bluetooth via M.2 2230 Slot (Realtek RTL8822CE) PXE (Pre-Boot Execution Environment) Support

WoL (Wake On Lan) Support

Audio Integrated Realtek High Definition Audio CODEC ALC892

Windows Server 2019

Windows 10 IoT Enterprise

Operating Systems Windows 10 (64-bit)

Ubuntu Linux

Please contact us directly for any special requirements

Chassis Description Low Profile Rugged Aluminum Chassis



10 - 48V DC Input

Power Input

Dinkle 5ESDAM-03 Mating Connector

Rear Locking 3-Pin power Jack ideal for mobile applications No External AC Adapter included (optional AC supply available)

Dinkle 5ESDAM-03P Mating DC Connector

DVI to VGA Adapter

Included with System 4 Rubber Feet

Rear Panel

Dimensions

Wall Mount Bracket

* NOTE: Subject to change without notice

(2) USB 3.1 Gen 2 Ports

2 PS/2 ports for Keyboard & Mouse

2 x RS232 COM port

1x Gigabit RJ45 Network connection

Audio Line-Out Jack

1x DVI-I video connector

1x DisplayPort video connector Locking 3-Pin DC Power Input Jack

(4) USB 3.1 Gen 2 Ports

3 x 10/100/1000 RJ45 Network connections

Microphone Input Jack

Front Panel Hard Drive indication LED

Power LED Light Power-on button Reset button

5.83" x 10.00" x 1.65" (148.00mm x 254.10mm x 42.00mm) [W x D

XH.

Operating Temperature: 0 - 40C (32 to 104 F)

Environmental Storage Temperature: -20 to 60C

Relative Humidity: 20% ~ 90% (Operating & Non-Operating)

Warranty 2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer Note: Specifications are subject to change without notice.