

## PM-3500B - POWERFUL PANEL/WALL MOUNT INDUSTRIAL PC (10TH GEN)



# \$1,615.00 USD

### Panel/Wall/Tower Mount Industrial PC

- Powerful 10th Generation Intel® Core™ Processors
- Massive Storage Options up to 28TB & up to 64GB of RAM
  - M.2 NVME options
  - PCIe Expansion Slots for Add-In Cards
    - AC and DC Power Supply Options
  - Panel/Wall/Desk/Bench/Tower Mounting
  - Custom Built to your Exacting Specifications
    - 2-Year Warranty





#### **GALLERY IMAGES**







#### PRODUCT DESCRIPTION

The Stealth Model: PM-3500B is a multi-purpose Panel Mount PC designed for demanding 24/7 operations yet adequately priced to meet your budget. The durable chassis of this industrial computer allows for easy installation into control panels, consoles, cabinets, walls or it can be placed on a desk or bench top.

The PM-3500B utilizes the latest Intel® 10th Generation Core™ Processors, massive storage options (up to 28TB) & memory up to 64GB. Open PCI-e expansion slots are available for the installation of your expansion boards.

Stealth's Packmount PC systems are ideal for telephony, industrial control, plant automation,
Datacenter/ISPs, IoT (Internet of Things), IIoT (Industrial Internet of Things), networking, machine vision,
and data acquisition applications to name a few.

Stealth Panelmount PCs and Servers, prior to shipping each and every system is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.



**Processor** 

**Drive Bays** 

Removable Storage

**Expansion Slot(s)** 

Video

#### **ADDITIONAL INFORMATION**

Supporting Intel®'s 10th Generation Core™ Processors (Comet Lake)

Intel® Core<sup>™</sup> i3-10100 (4 Cores / 8 Threads, up to 4.30GHz)

Intel® Core $^{\text{TM}}$  i5-10400 (6 Cores / 12 Threads, up to 4.30GHz) Intel® Core $^{\text{TM}}$  i7-10700 (8 Cores / 16 Threads, up to 4.80GHz)

Intel® Core™ i9-10900 (10 Cores / 20 Threads, up to 5.20GHz)

**Memory** 4 DDR4 Memory Sockets supporting up to 128GB RAM / Memory

Optional Onboard RAID configuration (0, 1, 5, 10), requires multiple

drives

(2) 5.25" Open Bay (For use with 5.25" Optical Drives, internal Hard

Drives, etc.)

(2) 3.5" Open Bay (for use with Floppy Drive, MO Drives, Tape

Drives or Hard Drives)

(1) 3.5" Internal optional cage for use with internal drive storage

Optional support for all Standard 5.25" Optical Disk Drives

Optional DVDRW/Blu-Ray Burner

Optional Removable drive bay with Key locking (uses 5.25"

expansion bay)

(1) PCIe 4.0/3.0 x16

(1) PCIe x1 3.0 Slot

(2) M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage

devices support (SATA & PCIE 3.0 x 4 mode)

1 x M.2 Socket 3, with M key, type 2242/2260/2280 (supports PCIE

4.0 x 4 mode) Note: this slot will be disabled if not used with an

11th Gen Processor.

1 x PCle x16 3.0 (max at x4 mode)

Includes DVI-D (Digital Only), HDMI 1.4/2.0 and DisplayPort (DP) 1.4

Intel® UHD Graphics 630

Supports triple-display simultaneously

Audio Onboard 8-Channel High Definition Audio CODEC

Networking Onboard Intel I219-V 1Gb Ethernet, RJ-45

Optional support for Fiber, 10GB, Wireless and more

TPM Module Optional TPM 2.0 (Trusted Platform Module), provides increased

hardware security.



**Ports** 

(2) USB 3.2 Gen 1 (rear mounted)

(2) USB 3.2 Gen 2 Type-A (rear mounted)

(2) USB 2.0 / 1.1 Ports (rear-mount)

(2) USB 2.0 / 1.1 ports (front-mount)

(1) RJ45 10/100/1000 BASE-T Gigabit LAN Port

(3) Audio Jacks (Input, Output and MIC)

(1) Combo PS/2 Port (Keyboard or Mouse)

(1) DVI-D (Digital Only)

(1) HDMI

(1) DisplayPort

Power Supply 100-240 VAC, 50Hz – 60Hz, 650W power supply (standard)

Meets 80PLUS Gold

Windows Server 2019

**Operating Systems** Windows 10 (64-bit)

Ubuntu Linux

Please contact us directly for any special requirements

**Cooling Fans** Smart Fan thermal management with 90CFM cooling fan.

**Environmental** Operating Temperature: 0 - 45C (32 to 113 F)

Rugged Steel Chassis, Panel, Wall, Bench/Tower configuration

Internal hold down bar for expansion cards

**Chassis Description** Full length front door with power and reset switch behind

thumbscrews door

Includes wall mount bracket

**Dimensions** 15.7" W x 7.0" H x " 16.5"D (398.78mm x 177.8mm x 419.1mm)

Weight Approx. 40 lbs. depending on configuration

Warranty 2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

**Disclaimer** Note: Specifications are subject to change without notice.