

#### LPC-490E - POWERFUL EXPANSION MINI PC WITH PCIE SLOT & MULTI GIGABIT LAN



# \$1,160.00 USD

#### Featuring a high performance Small PC with abundant network connectivity

- Powerful 8th Generation Intel® Celeron®, Pentium®, and Core<sup>™</sup> Processors
  - 10-48 VDC Operation, ideal for mobile/field
  - Includes 3-Pin locking power connector and
  - mobile hardware start-up and shutdown features
  - Built-in 4 Gigabit LAN, 4 USB 3.0, Audio, Serial, Video
    - Low Profile Rugged Aluminum Chassis
      - Slim Slot Loading Optical Drives
    - Solid State Hard Drives (SSD) optional
  - Windows 10, Windows 10 IoT, Server 2019, and Linux Compatible
    - RoHS, CE & FCC certified





## **GALLERY IMAGES**







## **PRODUCT DESCRIPTION**

The LPC-490E is a high performance Mini PC featuring a single PCIe x4 Expansion Slot, as well as a multitude of I/O including 4 RJ45 Gigabit LAN ports, DVI-I and DisplayPort video ports. It is offered with a range of Intel® Coffee Lake 8th Generation Processors up to Core<sup>™</sup> i7. All this power is packed into one tiny machine that is small enough to fit on the palm of your hand!

The LPC-490E Little PC is packed with features including a wide DC input range of 10-48V, a locking 3-Pin Power Jack, voltage power on sense (ideal for mobile applications), up to 2 Drives in a combination of 2.5" Hard Drives or Solid State Drives with optional onboard Raid support, an optional front slot loading Optical Drive or removable drive, up to 64GB memory, onboard audio, and much more.

Typical applications include:

- Instrumentation and Control
  - Security
  - Mobile & Vehicle PC
    - VPN
  - Network Appliance
    - Kiosk
    - Data acquisition
  - IoT (Internet of Things)
    - Mini Servers

The LPC-490 series adds to Stealth's robust lineup of Small Form Factor Mini PCs designed to fit in spaceconfined areas and are ideal for demanding applications within the Industrial, Commercial, Military & Defense, Scientific Research, Public Safety, Utility, Transportation, Mining and Telecommunications markets.



### **ADDITIONAL INFORMATION**

Processor	Intel® Celeron® G4900T (2 Cores / 2 Threads, 2.9Ghz) Intel® Pentium® Gold G5400T (2 Cores / 4 Threads, up to 3.1Ghz) Intel® Core <sup>™</sup> i3-8100T (4 Cores / 4 Threads, 3.10Ghz) Intel® Core <sup>™</sup> i5-8500T (6 Cores / 6 Threads, up to 3.5Ghz) Intel® Core <sup>™</sup> i7-8700T (6 Cores / 12 Threads, up to 4.00Ghz)
Chipset	Intel® Q370 Chipset (Coffee Lake)
Memory	2x DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory
Internal Storage	Optional Onboard RAID configurations (0, 1), requires multiple drives SATA III (6Gb/s and 3Gb/s) support Optional Solid State Disk Drive (SSD)
Internal Expansion Option	2 Internal Mini-PCIe expansion options (1) full sized, (1 half size)
Optical Drives	Optional 2.5" Removable Drive Bay Optional Slim Slot Loading DVD-RW / CD-RW (SATA) Optional DVD-RW / Blu-Ray Burner Serial ATA (SATA)
Video	Intel® HD Graphics 610 (Intel® Celeron and Pentium Processors) Intel® HD Graphics 630 (Intel® 8th and 9th Generation Processors) Includes DVI-I & DisplayPort video ports
Networking	<ul> <li>(1) Integrated 10/100/1000 Base-T Intel® i219LM</li> <li>(3) Integrated 10/100/1000 Base-T Intel® i211AT</li> <li>PXE (Pre-Boot Execution Environment) Support</li> <li>WoL (Wake On Lan) Support</li> <li>Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless</li> <li>Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal</li> <li>Mini-PCle</li> </ul>
Expansion Slot(s)	1 x PCIe x4 Version 2.0 Compliant card up to 8.5"
Audio	Integrated Realtek High Definition Audio CODEC ALC892
Operating Systems	Windows Server 2019 Windows 10 IoT Enterprise Windows 10 (64-bit) Ubuntu Linux Please contact us directly for any special requirements



<b>Chassis Description</b>	Low Profile Rugged Aluminum Chassis
Power Input	10 – 48V DC Input Dinkle 5ESDAM-03 Mating Connector Rear Locking 3-Pin power Jack ideal for mobile applications No External AC Adapter included (optional AC supply available)
Included with System	Dinkle 5ESDAM-03P Mating DC Connector DVI to VGA Adapter 4 Rubber Feet Wall Mount Bracket * NOTE: Subject to change without notice
Rear Panel	<ul> <li>(2) USB 3.1 Gen 2 Ports</li> <li>2 PS/2 ports for Keyboard &amp; Mouse</li> <li>2 x RS232 COM port</li> <li>1x Gigabit RJ45 Network connection</li> <li>Audio Line-Out Jack</li> <li>1x DVI-I video connector</li> <li>1x DisplayPort video connector</li> <li>Locking 3-Pin DC Power Input Jack</li> </ul>
Front Panel	<ul> <li>(4) USB 3.1 Gen 2 Ports</li> <li>3 x 10/100/1000 RJ45 Network connections</li> <li>Microphone Input Jack</li> <li>Hard Drive indication LED</li> <li>Power LED Light</li> <li>Power-on button</li> <li>Reset button</li> </ul>
Dimensions	5.81" x 10.00" x 2.83" (147.6mm x 254.1mm x 71.8mm) [W x D x H]
Environmental	Operating Temperature: 0 – 40C (32 to 104 F) Storage Temperature: -20 to 60C Relative Humidity: 20% ~ 90% (Operating & Non-Operating)
Warranty	2 Year limited Warranty, Standard 1 Year Extended Warranty available (see Configurator/Price List)
Disclaimer	Note: Specifications are subject to change without notice.