

LPC-860 - RUGGED FANLESS, MINI PC WITH DUAL REMOVABLE DRIVES



\$1,710.00 USD

Powerful, Rugged & Versatile Fanless PC

- No noise, Rugged Fanless Chassis
- Powerful Intel's® 6th and 7th generation Core™ i5 & i7 mobile processors
 - 8x DIO (Digital input/output) ports
 - Dual Removable Front Drives
- Wide Range 9-48 VDC Input, ideal for mobile/field
- Built-in Gigabit LAN, USB 3.0/2.0, Audio, Serial, Video (DVI-I & Displayport)
 - 4K Resolution, Ultra HD, Triple Display support
 - Solid State Drives (SSD) Standard
 - Windows 7, 8.1, 10 and Linux
 - CE, FCC & RoHS
- See our FAQ - Why Choose Fanless?
- Rackmount model version also available



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth LPC-860 is a powerful yet silent workhorse, housed in a heat-dispersing, dust-repellent aluminum chassis so quiet you could hear a pin drop - even at full operational capacity.

This rugged fanless mini PC designed for high performance is well equipped with Intel's® 6th and 7th generation Core™ i5 & i7 mobile processors, supporting up to 32GB of DDR4 RAM and capacity of up to 8TB in solid state drives(SSD) when equipped with 4 internal drives.

This LPC-860 mini PC includes, two Removable Front Drive Bays, providing easy drive swapping and optional RAID configurations. The powerful small form factor pc also includes an abundance of I/O ports such as USB 3.0/2.0 ports, RS232 COM ports, Gigabit networking, external SIM card sockets for wireless connectivity and audio/video ports.

Stealth's LPC-860 small pc is designed to handle 4K Ultra HD Resolution video and can support up to three connected displays via DisplayPort and DVI-I video ports. The LPC-860 also features 8x DIO (Digital input/output) with Isolation, offering the advantage of providing electrical isolation of digital signals.

Stealth developed the LPC-860 to be more than just your average mini PC, it engineered to be extremely mobile application friendly with the inclusion of Wide Range 9-48 VDC power input and to protect the system the power is regulated with OVP (Over Voltage Protection), OCP (Over Current Protection) & Reverse Protection.

The LPC-800 series is RoHS, CE & FCC certified, and designed for use in a multitude of applications including: Audio/Video Recording, Embedded Control, Digital Signs, Interactive Kiosks, Thin-Clients, and Human/Machine Interface.

ADDITIONAL INFORMATION

Processor	Intel® Core™ i7-7700T (4 Cores / 8 Threads, up to 3.80Ghz) Supporting Intel® 6th Gen Core™ Processor i5-6500TE, Quad Core, 6MB Cache, up to 3.3 GHz (standard) Optional Intel® 6th Gen Core™ Processor i7-6700TE , Quad Core, 8MB Cache, up to 3.4 GHz
BIOS	AMI 128Mbit SPI BIOS
Chipset	Intel® Q170 Express Chipset
Memory	2x DDR4 Memory Sockets Supporting up to 32GB of RAM / Memory
Internal Storage	256GB 3D NAND SSD (Solid State Drive) standard (SATA) Options of up to 2TB SSD internal storage. Optional Onboard RAID configurations (0, 1, 5, 10), requires multiple drives
Internal Expansion Option	4 Internal full sized Mini-PCIe expansion slots
Video	Integrated Intel HD Graphics 530 Includes DVI-I & 2x DisplayPort video ports Supports 4K Ultra HD Resolution as well as 1080p HD Video Triple Display support with DisplayPort and DVI-I Max Resolution, DisplayPort Mode: 4096×2304 @ 60Hz, DVI Mode: 1920 x 1200 @ 60Hz Optional 4/8 x 10/100/1000 RJ45 POE Network connections on Front Panel
Networking	2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported LAN1: Intel I210-AT, LAN2: Intel I219LM Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe
Communications	2x External SIM card sockets for wireless connectivity
Audio	Integrated Realtek High Definition Audio CODEC ALC888S

Operating Systems	Windows Server 2019
	Windows 7 (32 and 64-bit)
	Windows 10 (64-bit)
	Windows 8.1 (32 and 64-Bit)
	Ubuntu Linux
	Please contact us directly for any special requirements
TPM Module	TPM 2.0 (Trusted Platform Module), provides increased hardware security.
WatchDog Timer	1 ~ 255 sec/min
	System Reset
Hardware Monitor	Processor temperature
	Voltage
Chassis Description	Fanless Rugged Aluminum Chassis
	Input is 9V – 48V DC
	Power Mode: AT & ATX
Power Input	Rear Locking 3-Pin power Jack ideal for mobile applications
	Includes External AC Adapter, Input 100~240V AC @ 1.4A 50-60Hz
	Power Protection: OVP (Over Voltage Protection), OCP (Over Current Protection) & Reverse Protection
	North American Power Cord
	Wall Mount Bracket
Included with System	* NOTE: Subject to change without notice
	100-240V AC Adapter, 4.75ft cable exit length
	Optional 4/8 x 10/100/1000 RJ45 POE Network connections on Front Panel
	Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth, Intel® AC7260 via internal Mini-PCIe
Options	Remote power option Ideal for OEM or Cabinet manufacturers
	External USB DVD+-RW/CD-RW Drive
	2 x RS232 COM port
	2x Gigabit RJ45 Network connection
	8x DIO (Digital input/output) with Isolation
Rear Panel	Audio Line-Out Jack
	Microphone Input Jack
	4 x USB 3.0 Ports
	1x DVI-I video connector
	2x DisplayPort video connectors
	9 – 48V DC Connector

Front Panel

2 x USB 3.0 Port
2 x USB 2.0 Ports
AT / ATX Switch
Power-on button

Dimensions

9.44"(W) x 10.27"(D) x 3.11"(H) (240mm x 261mm x 79mm)

Environmental

Operating Temperature: 0 - 40C (32 to 104 F)
Relative Humidity: 10% ~ 95%, non-condensing (Operating & Non-Operating)
Shock: 50G, half sine, 11ms (with SSD)
Vibration: 5 Grms, 5 - 500 Hz, 0.5 hr/axis (with SSD)
Vibration: 1 Grms, 5 - 500 Hz, 0.5 hr/axis (with HDD)

Approvals

RoHS
CE
FCC

Weight

Unit Weight: 8.0 lbs / 3.62 KG (Depending on configuration)

Warranty

2 Year limited Warranty, Standard
1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.