

## WPC-905 - HIGH PERFORMANCE RUGGED FANLESS WATERPROOF PC



# \$3,240.00 USD

# A Completely Sealed Mobile PC for Harsh Environment and Marine Applications

- Waterproof / Water Resistant
- Dust, rain and splash resistant, Sealed to IP67 specifications
  - Fanless Noise Free, Low Power Consumption
- Powerful 8th Generation Intel® Celeron®, and Core™ Processors
  - DC Input, Wide Range 9 48VDC
- Solid State Hard Drives (SSD) with optional RAID configurations
  - Small Form Factor design
  - Windows 10, Server 2019, and Linux compatible
  - RoHS, CE & FCC, EN50121-3-2, EN50155 certified





#### **GALLERY IMAGES**







#### PRODUCT DESCRIPTION

The new Stealth WPC-905 is a high performance rugged Waterproof PC computer that is completely sealed, surviving liquids, chemicals, dust and dirt intrusion and meeting IP67/NEMA 6 environmental specifications. Designed without cooling fans the rugged chassis acts as a heat sink to dissipate internal heat and provide noise free operation.

This durable environmentally sealed small form PC features powerful 8th Generation Intel® Celeron®, and Core™ Processors, solid state drives (SSD) with optional onboard RAID configurations and operates from a wide range of DC input power (9 - 48VDC) making it a perfect fit for mobile and transportation based applications.

The WPC-905 is RoHS, CE & FCC, EN50121-3-2, EN50155 certified and also incorporates TPM 2.0 (Trusted Platform Module) to provide increased hardware security.

Stealth's Waterproof PC products are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Marine, IoT, Industrial Internet of Things (IIoT),

Transportation, Mining and Telecommunications markets.



## **ADDITIONAL INFORMATION**

Supporting Intel®'s 8th Generation Core™ Processors

Intel® Celeron® 4305UE (2 Cores / 2 Threads, 2.00 GHz)

Processor Intel® Core™ i3-8145UE (2 Cores / 4 Threads, up to 3.90 GHz)

Intel® Core™ i5-8365UE (4 Cores / 8 Threads, up to 4.10 GHz)

Intel® Core™ i7-8665UE (4 Cores / 8 Threads, up to 4.40 GHz)

Chipset Intel® SoC (Cannon Lake)

**Memory** (1) DDR4 SO-DIMM Memory Slot, up to 32GB

Options of up to 2TB SSD internal storage.

2 x 2.5" Internal Drive bays

**Internal Storage** Optional Onboard RAID configurations (0, 1), requires multiple

drives

Optional (1) mSATA drive support

**Internal Expansion Option** 1 Full size Mini-PCle slot, supports PCle, mSATA and USB interface

Intel® UHD Graphics 620 (Intel® 8th Generation Processors)

Video Intel® HD Graphics 610 (Intel® Celeron and Pentium Processors)

DVI-D max. resolution 1920 x 1200 @ 60 Hz

Intel® iAMT 11.0 Supported (LAN 1)

M12 Connector, X-coded

Networking LAN1: Intel® I219LM, LAN2: Intel® I210

PXE (Pre-Boot Execution Environment) Support

WoL (Wake On Lan) Support

**Audio** No Audio Support

TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware

security.

Windows Server 2019 Windows 10 (64-bit)

Operating Systems

Ubuntu Linux

Please contact us directly for any special requirements

Rugged Aluminum Chassis

Vesa 75mm/100mm Mounting on bottom

Chassis Description Completely Sealed Water, dust & debris Proof enclosure

Fanless Design

Fully IP67/NEMA 6 rated, Highest level for Dust and Water Proof



M12 Connector, A-coded **Power Input** 

Input is 9V - 48V DC

Processor temperature

**Hardware Monitor** System temperature

Voltage

(1) DVI-D IP67 Connector

(1) Power input port, M12, A-Coded

(1) RS-232 Serial Port, M12, A-Coded

(2) 2-port USB 2.0 ports, M12, A-Coded

(2) Network ports, M12, X-Coded

(6) Water tight M12 Connectors

Power and Hard Drive notification LED

Power-on button

**Dimensions** 9.8" x 7.1" x 1.7" (250mm x 180mm x 44mm) [W x D x H]

Operating Temp: -30°C to 70°C (-22°F to 158°F)

Relative Humidity: 95% @ 70°C **Environmental** 

Storage Temp: -40°C to 85°C (-40°F to 185°F)

Humidity: 5% ~ 95%, non-condensing (Operating & Non-Operating)

EN50121-3-2

EN50155

**Approvals RoHS** 

**Rear Panel** 

**Front Panel** 

Shock

CE **FCC** 

Operating: 15g/11ms, ½ sine, 3 shocks in +ve and -ve direction, all

3 axes (IEC 60068-2-27)

Storage: 50g/11ms, ½ sine, 3 shocks in +ve and -ve direction, all 3

axes (IEC 60068-2-27)

Weight Unit Weight (w/o cables): 5.1 lbs. / 2.32kgs.

2 Year limited Warranty, Standard Warranty

1 Year Extended Warranty available (see Configurator/Price List)

Includes additional (1) Watertight DVI cable

Includes set of (6) watertight cables with mating M12 connectors

**Included with System** 100-240V AC Adapter

North American Power Cord

Wall Mount Bracket

Disclaimer Note: Specifications are subject to change without notice.