

17" ALL WEATHER LCD MONITOR, SUNLIGHT READABLE DISPLAY



\$2,795.00 USD

Model: SVM-1700-RT-USB

- 17" Sunlight Readable Marine LCD Monitor
 - 1,000 Nits (Cd/m2) High Brightness
 - 9 to 36VDC Power Input
 - NEMA 4, IP65 Sealed Front Panel
- Operates in -10 to +50C temperatures
 - VGA, DVI & Composite Video Inputs
 - Front Brightness Controls
 - Picture in Picture Capability
 - Low Power LED Backlighting
- Touch Screen (Resistive Touch Standard)



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model SVM-1700 is a 17" sunlight readable LCD monitor ideal for use in direct sunlight or high ambient light conditions. Typical applications would be for marine, industrial, security, kiosks, vehicles or outdoor displays as the LCD's front panel is environmentally sealed to NEMA 4/IP65. Stealth's SVM-1700 features a front adjustable brightness control knob allowing for the LCD to be adjusted to low levels for night operation and a full 1000 nits for daytime bright sunlight conditions. Front controls also include picture-in-picture, night mode, video inputs, contrast etc. All Stealth monitors are available with touch screen capability or anti-glare glass for maximum protection.

The SVM-1700 operates from 9 to 36VDC which makes it ideal for marine and in vehicle applications. Stealth's 17" sunlight readable LCD features a wide range of video inputs that include dual VGA and DVI as well as 3 composite (NTSC) RCA input connectors.

ADDITIONAL INFORMATION

Screen Size	17.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.297mm x 0.297mm
Response Time	3.5ms (Rise time), 1.5ms (Decay time) typical
Type	LCD c/w LED Backlighting
Video Input Connectors	2x Analog VGA / HD-15 2x Digital DVI 3x Composite
Touchscreen Interface	1x USB 2.0
Viewing Angle	160° / 160° (H / V)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	1000 cd/m2 typical at center (1000 Nits) (adjustable)
Viewable Image Size	Horizontal: 13.3" / 337.92 mm, Vertical: 10.6" / 270.34 mm
Input	9V – 36V DC Input via Terminal Block Power Consumption: 35~40W typical (Note: an AC/DC Power Adapter is optional)
Control Buttons (Front mounted)	PIP, Brightness, Night Mode, Down, Menu, Up, Input, Power
Picture In Picture Options (PiP)	Available with Child, Split or Wide Screen.
LCD Mounting Options	Designed for Panel Mount (Flush Mount) VESA 100mm or 75mm mount (Note: VESA mounting not available if external AC/DC power adapter is used)
Environmental Rating	Standard Bezel: NEMA 4 / IP65 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water

Environmental

Operating Temperature: -10 to 50C (14 to 122 F)

Storage Temperature: -20 to 70C (-20 to 158F)

Approvals

Meets ICE 60945 BV Marine and IACS-E10

RoHS

Available Models

SVM-1700-RT-USB – Resistive Touch with USB Interface

Unit Weight

Unit Weight: 10.25 Pounds (4.64Kg)

Dimensions

15.15"(W) x 13.7"(H) x 2.24"(D) (385mm x 348mm x 57mm)

Warranty

1 Year Parts & Labor