

75-DT-BL - RUGGED ILLUMINATED/BACKLIT KEYBOARD



\$349.00 USD

Small Desktop Backlit Keyboard

- Sealed to NEMA 4, 4X / IP65 specifications
 - Backlit / Illumination
 - Small Foot Print Design
 - 75 Keys including 12 Function Keys
- Greater than 10 Million cycles expected life
 - PS/2 or USB connectors



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model 75-DT-BL is a NEMA 4, 4X / IP65, waterproof, dust-proof, and backlit keyboard that is ideal for industrial, kiosk and mobile computing applications. It is a highly versatile keyboard that offers a high value solution for a low price and offers both USB and PS/2 interfaces.

The 75-DT-BL features red LEDs providing bright keyboard illumination ideal for dark or low light areas.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 135g (+/- 30g), 4.76 oz. +/- 1.06 oz.

Feedback: Tactile with mechanical snap

Power

PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port)

USB Keyboard: 200mA @ 5V from USB port

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% Humidity Resistant

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Backlighting / Illumination

Red LEDs (On/Off)

Dimensions

8.25" (w) x 4.34" (h) x 1.08" (d) [209.6mm x 110.2mm x 27.4mm]

Cable

Length: 10' (3.04 meters)

Compatibility

Compatible with all Windows Operating Systems

Warranty

1 Year Parts & Labor

Model Numbers

75-DT-BL-PS/2 - PS/2 Interface

75-DT-BL-USB - USB Interface

Disclaimer

Note: Specifications are subject to change without notice.