

## 880-DP-TP-BL - SMALL FOOTPRINT KEYBOARD WITH BUILT-IN TOUCHPAD MOUSE



**\$395.00 USD**

### ***Sealed Illuminated Keyboard/Mouse***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Backlit / Illumination
  - ABS-Polycarbonate Sealed Case
  - Small Foot Print Design
- 86 Keys, 12 Function Keys, Emergency Key
  - Built-in Touchpad Mouse
- Greater than 10 Million cycles expected life
  - PS/2 or USB connectors



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model 880-DP-TP-BL offers both a rugged keyboard and rugged touchpad mouse in one compact package. It boasts a completely sealed and ruggedized construction that allows it to meet NEMA 4X / IP65 specifications.

The 880-DP-TP-BL's backlighting is available with Red LEDs and provides bright keyboard illumination. Additionally, the 880-DP-TP-BL features a specially designed Emergency key that when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. The 880-DP-TP-BL is available with PS/2 or USB connectors.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

## ADDITIONAL INFORMATION

### Industrial Approvals

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

### Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port)

### Power

PS/2 Mouse: 10mA @ 5V (from mouse port)

USB: 210 mA @ 5V (from USB port)

### Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

### Humidity

100% Humidity Resistant

### Shock

3x11 ms pulses of 50g on each of 3 axes

### Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

### Backlighting / Illumination

Red LEDs (On/Off)

### Dimensions

11.39" (w) x 7.30" (h) x 1.87" (d) [289.56mm x 185.56mm x 47.24mm]

### Cable

Design: 4 Feet (1.2 meters) Single 4' "Y-Split" Coiled Cable with PS/2 Connectors, or Single USB Cable

### Compatibility

PS/2: All windows operating systems most Linux/Unix Systems, USB:

All windows operating systems, MAC OS and most Linux/Unix Systems

### Warranty

1 Year Parts & Labor

### Model Numbers

880-DP-TP-BL-PS/2-RED - PS/2 interface, Red Backlight

880-DP-TP-BL-USB-RED - USB Interface, Red Backlight

### Disclaimer

Note: Specifications are subject to change without notice.