

## 880-PM-FSR-BL - SMALL FOOTPRINT PANELMOUNT KEYBOARD



**\$395.00 USD**

### ***Small Panelmount keyboard, w/ Built-in Mouse***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
  - Backlighting / Illumination
- ABS-Polycarbonate Sealed Plastic Case with 4-40 Mounting Studs
  - Small Foot Print Design
- 86 Keys, 12 Function Keys, Emergency Key
- Built-in 3 button FingerTipMouse (Pointing Device)
  - Greater than 10 Million cycles expected life
  - PS/2 or USB connectors



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth Computer model 880-DP-FSR-BL offers both a rugged keyboard and pointing device in one compact package. It boasts a completely sealed and ruggedized construction that allows it to meet NEMA 4, 4X / IP65 specifications. The small footprint keyboard also features a mounting hole pattern for easy installation in mobile computing applications.

The 880-DP-FSR-BL's backlighting is available with red LEDs and provides bright keyboard illumination. Additionally, the keyboard also features a specially designed Emergency key that when pressed, sends a signal of Shift+F1. The 880-DP-FSR-BL is available with a USB or PS/2 connector.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

## ADDITIONAL INFORMATION

<b>Industrial Approvals</b>	NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B
<b>Key Switch</b>	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
<b>Power</b>	PS/2 Keyboard: 160mA @ 5V (from keyboard Port) PS/2 Mouse: 55mA @ 5V (from mouse port) * PS2 Current ratings valid only when both keyboard and mouse are connected USB Keyboard / Mouse: 215mA @ 5V from USB port
<b>Temperature Range</b>	Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
<b>Humidity</b>	100% (when properly installed)
<b>Shock</b>	3x11 ms pulses of 50g on each of 3 axes
<b>Vibration</b>	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
<b>Backlighting / Illumination</b>	Red LEDs, 4 levels (On/Off, 1, 2, 3, 4)
<b>Dimensions</b>	(W-H-D) 11.8" x 6.79" x 1.35" (299.7mm x 172.5mm x 12.5mm)
<b>Cable</b>	Design: 4 Feet (1.2 meters) Single 4' "Y-Split" Coiled Cable with PS/2 Connectors, or Single USB Cable
<b>Compatibility</b>	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
<b>Additional Options</b>	Custom cable lengths, special connectors, custom enclosures etc Other Languages Available - Contact us for more details, Minimum quantities may apply.
<b>Warranty</b>	1 Year limited Warranty Standard
<b>Model Numbers</b>	880-PM-FSR-BL (PS/2 Interface) 880-PM-FSR-BL (USB Interface)

## Disclaimer

Note: Specifications are subject to change without notice.