

### 5000-DT-FSR-NI - NON-INCENDIVE DESKTOP KEYBOARD



# \$795.00 USD

## Sealed Non-Incendive Safe Keyboard, w/ Built-in Mouse

- Non-Incendive for use in hazardous environments
- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Rugged Stainless Steel Case
  - Includes Bulkhead Connectors
  - 112 Keys, 20 Function Keys, WIN KEY
    - Built-in 3 button Pointing Device
  - Greater than 10 Million cycles expected life
- Includes separate PS/2 or USB cables with Bulkhead connectors





#### **PRODUCT DESCRIPTION**

The Stealth model 5000-DT-FSR-NI is a Non-Incendive Desktop Keyboard that is environmentally sealed to NEMA 4, 4X / IP65 specifications and designed to operate in hazardous locations including wet, dirty or harsh environments.

This rugged keyboard with stainless steel bezel includes 112 Keys in total, 20 Function Keys, 22 Key numeric keypad and a built-in 3 button pointing device mouse. The 5000-DT-FSR-NI has a Factory Mutual approval for Class I, Division II, Groups A, B, C, and D. All units include isolation barrier.

The 5000-DT-FSR-NI is available with a USB or PS/2 interface.



## **ADDITIONAL INFORMATION**

FM Approved for Class I

**Industrial Approvals** Division II, Groups: A, B, C, D

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Material: Industrial Silicone Rubber Life: Greater than 10 million cycles

**Key Switch** Travel: 0.060" (1.5mm)

Humidity

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

Temperature Range Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)

100%

**Shock** 3×11 ms pulses of 50g on each of 3 axes

Vibration Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

**Dimensions** (W-H-D) 16.25" x 7.9" x 1.9" (412.8mm x 200.7mm x 48.3mm)

Length: 5 feet from keyboard to Bulkhead Connector

**Cable** Design: separate cables

(providing separate keyboard and mouse connections)

**Compatibility** Compatible with all Windows Operating Systems

Weight Unit: 5.25 lbs +/- 0.10 lbs (2.38 kg +/ 0.05 kg)

Warranty 1 Year limited Warranty Standard

**Model Numbers** 5000-DT-FSR-NI-PS/2 (PS/2 Interface)

**Disclaimer** Note: Specifications are subject to change without notice.