

#### **5000-OEM-FSR - OEM/OPEN-FRAME KEYBOARD**



# \$440.00 USD

#### Open-Frame keyboard, w/ Built-in Mouse

- Meets NEMA 4, 4X / IP65\* When properly installed
- 112 Keys, 20 Function Keys, 22 Key numeric keypad
  - Built-in 3 button FingerTipMouse (Pointing Device)
    - "CLEAN KEY" disengages keys for easy cleaning
      - Greater than 10 Million cycles expected life
  - Includes 10' straight cable (PS/2 or USB interface)





### **PRODUCT DESCRIPTION**

The Stealth Computer model 5000-OEM-FSR combines a 112-key keyboard and built-in FingerTipMouse (pointing device) into a single, fully integrated unit. Each kit is comprised of an industrial silicone keypad, switch matrix board, keyboard controller, and cables. This keyboard also offers users the Windows keys for easy access to system shortcuts and features a "Clean Key" that locks the keyboard down when a cleaning function is performed.



## **ADDITIONAL INFORMATION**

Industrial Approvals	NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B * Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65)
Key Switch	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
Power	PS/2 Keyboard: 35mA @ 5V (from keyboard Port) PS/2 Mouse: 5mA @ 5V (from mouse port) * PS2 Current ratings valid only when both keyboard and mouse are connected USB Keyboard / Mouse: 40mA @ 5V from USB port
Temperature Range	Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
Humidity	100% (when properly installed)
Shock	$3 \times 11$ ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Dimensions	(W-H-D) 15.0" x 6.5" x 0.42" 381.0mm x 165.1mm x 10.7mm
Cable	Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable
Compatibility	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
Warranty	1 Year limited Warranty Standard
Model Numbers	5000-OEM-FSR-USB (USB Interface) 5000-OEM-FSR-PS/2 (PS/2 Interface)
Disclaimer	Note: Specifications are subject to change without notice.