

KYBX-400-PM-BL-TB-USB - VANDAL RESISTANT PANELMOUNT KEYBOARD



\$650.00 USD

Vandal Resistant Panelmount Keyboard with Built-in Trackball Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - Rugged, Vandal Resistant Panelmount Keyboard
 - NVIS-compliant Red Backlighting
 - 10 Million Actuations Expected life
 - 71 Full Travel, Tactile Laser Etched Keys
 - Includes 5.75' USB cable
 - Desktop version also available.



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model KYBX-400 series keyboard is an industrial grade Vandal Resistant Panelmount Keyboard with built-in optical trackball that is environmentally sealed to NEMA 4, 4X, IP65 specifications when installed properly. This rugged keyboard is housed in a rugged vandal resistant enclosure and will stand up to harsh, wet and dirty environments.

This Stealth keyboard features 71 full-travel keys with silent tactile feedback for fast and accurate data input functionality. The 38mm optical trackball is sealed to NEMA 4, 4X / IP65 environmental specifications and offers a superior resolution of 800DPI.

Stealth's line of rugged kiosk/indestructible Keyboards also features NVIS-compliant red backlighting, which makes this keyboard ideal for military, aviation or vehicle applications where night vision goggles are worn. Ideal applications include in vehicle computing, plant floor, kiosks, control rooms, warehousing and outdoor environments to name a few.

ADDITIONAL INFORMATION

Industrial Approvals	Meets NEMA 4, 4X, IP65 when installed properly* RoHS Compliant, CE and FCC
Key Switch	Material: Polymer Style: Protuberant rectangular keys Life: >10 million actuations Travel: 2.00mm (0.07") Contact: Carbon-on-Gold key switch PCB Trackball: 38mm (1.5") diameter 800 DPI IP65 Optical Trackball Mouse
Power	Supply Voltage: +5V DC +/-5% Current Rating: Approx. 30mA Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
Temperature Range	Atmospheric pressure: 60-106Kpa. Saline mist: 96 hours, IEC 60512-6 Damp heat test at + 40oC: 21 days, IEC 60512-6 Dry heat test at + 85oC: 10 days, IEC 60512-6
Humidity	30-90%
Housing	Rugged, Vandal Resistant Stainless Steel casing Sealed to NEMA 4, 4X, IP65 when installed properly
Backlighting / Illumination	NVIS-compliant red backlighting, ideal for military, aviation or vehicle applications
Dimensions	(W-H-D) 14.96" x 4.64" x 1.43" (380.0mm x 118mm x 36.5mm)
Cable	Length: 5.75 feet (1.75m) Design: Single Cable USB
Compatibility	Compatible with all Windows Operating Systems
Warranty	1 Year limited Warranty Standard
Model Numbers	KYBX-400-PM-BL-TB-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.