

#### **1330-FTM-OEM - OEM/OPEN-FRAME POINTING DEVICE**



# \$169.00 USD

#### Small, Open-Frame Mouse

Meets NEMA 4, 4X / IP65 specifications when properly installed

• Two-button OEM/Open-Frame FingerTipMouse pointing device in a compact design

- Built-in 3 button FingerTipMouse (Pointing Device)
  - 10 Million cycles expected life
    - Ideal for Kiosk Applications
  - Includes 10' cable PS/2 or USB interface





### **PRODUCT DESCRIPTION**

The Stealth Computer model 1330-FTM-OEM is a smaller version of our regular FingerTipMouse pointing device. The two-button device offers the versatility and convenience of the FingerTipMouse pointing device but in a compact version to suit a variety of applications including industrial environments.

The 1330-FTM-OEM when properly installed is dustproof, waterproof, and non-corrosive.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.



## **ADDITIONAL INFORMATION**

Industrial Approvals	NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B * Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65)
Key Switch	Actuation Force: 7oz (200g) Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Feedback: Tactile with mechanical snap
Power	PS/2: 35mA @ 5V (from mouse Port) USB: 35mA @5V (from USB port)
Temperature Range	Operating: -40C to +70C (-40F to +158F) Storage: -40C to +90C (-40F to +194F)
Humidity	100% Humidity Resistant when properly installed
Shock	3×11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Dimensions	(W-H-D) 3.10" x 1.40" x 0.45" (78.7mm x 35.6mm x 11.4mm)
Cable	Length: 10 feet (3.94 meters), Interface: Either PS/2 or USB single connection
Compatibility	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
Warranty	1 Year limited Warranty Standard
Model Numbers	1330-FTM-OEM-USB (USB Interface) 1330-FTM-OEM-PS/2 (PS/2 Interface)
Disclaimer	Note: Specifications are subject to change without notice.