


FTM-DT-FSR - DESKTOP INDUSTRIAL POINTING DEVICE



\$250.00 USD

Desktop Industrial Fingertip Mouse

- Desktop or Bench Top style
- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
 - Rugged Sealed Stainless Steel
- 3-Button Mouse design, Right Left & Center / Middle buttons
- Pressure Sensitive Sensor for positive motion control, 360 Degree Movement
 - 10 Million cycles expected life
- Includes 10' cable PS/2 or USB interface



PRODUCT DESCRIPTION

The Stealth FTM-DT-FSR is an environmentally sealed, NEMA 4, 4X / IP65, desktop pointing device that is designed to operate in wet, dirty or harsh environments. Housed in water-tight durable stainless steel enclosure, this industrial grade pointing device combines the functionality of a mouse with the ease of a joystick in a small tough package.

The FTM-DT-FSR is available with USB or PS/2 cable sets. All of Stealth's industrial grade keyboards and pointing devices are plug-and-play compatible with Windows operating systems and require no special drivers.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
Key Switch	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
Power	PS/2: 35mA @ 5V (from mouse Port) USB: 35mA @5V (from USB port)
Temperature Range	Operating: -20C to +70C (-4F to +158F) Storage: -40C to +70C (-40F to +158F)
Humidity	100% Humidity Resistant when properly installed
Shock	3×11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Dimensions	(W-D-H) 4.9" x 4.9" x 1.13" (124.5mm x 124.5mm x 28.7mm)
Cable	Length: 10 feet (3.94 meters), Design: PS2 or USB
Compatibility	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
Warranty	1 Year limited Warranty Standard
Model Numbers	FTM-DT-FSR-PS/2 (PS/2 Interface) FTM-DT-FSR-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.