

17" 4K LCD MONITOR / KEYBOARD 1U RACK DRAWER (FR-1010-17W-4K)



\$2,355.00 USD

Model: FR-1010-17W-4K

- 17.3" Slim 1U Rack LCD / Keyboard / Mouse
- 4K UHD, 3840 x 2160 native resolution, Widescreen (1920 x 1080 & 1920 x 1200 support)
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
 - Built-in Keyboard & Touch Pad
- DisplayPort or optional HDMI Video input
 - Built-in lockable Slide Rails
 - Optional 8 & 16 port KVM
- Optional 12/24/48/125/250V DC power



GALLERY IMAGES



PRODUCT DESCRIPTION

Slim 1U All-In-One 4K Widescreen Display/Keyboard in a Drawer

Stealth's 17" 4K LCD Monitor / Keyboard 1U Rack Drawer has been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

The model FR-1010-17W-4K features a widescreen 17" 4K LCD monitor with a 3840 x 2160 native resolution and comes equipped with built-in keyboard and a track pad mouse connecting to a USB interface. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of 12/24/48/125/250VDC are also available.

Other FlatRack 1U & 2U Rack Drawer models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	17.3" (Diagonal)
Type	LCD c/w LED Backlighting
Aspect Ratio	16:9
Native Resolution	3840 x 2160 (Auto sync from 640 x 480 to 3840 x 2160)
Pixel Pitch	0.0995mm x 0.0995mm
Response Time	16ms Typical
Viewable Image Size	Horizontal: 15.04" / 382.12mm, Vertical: 8.46" / 214.94mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	DisplayPort (Standard) HDMI (Optional)
Viewing Angle	89 (up), 89 (down), 89 (left), 89 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Power Consumption: Max. 29W, Standby 9W Internal 100~240VAC, 50/60Hz Power Supply Dual USB connectors for Keyboard and Mouse
Built-in Keyboard / Mouse	104 Keys 2 Button Touch Pad
Audio	2x2 W Speaker
Environmental	Operating Temperature: 0~55C (32~131F) Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Storage Temperature: -20~60C (-4~140F) Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration

Color	Black (standard)
Unit Weight	Unit Weight: 24 lbs (10.8 Kgs)
Additional Options	HDMI 2.0 / HDCP 2.2 Optional 12/24/48/125/250V DC power KVM version with 8 or 16 inputs available FR-1010-17W-4K-DP-USB (DisplayPort + Internal 100~240VAC, 50/60Hz) FR-1010-17W-4K-DP-USB-12V (DisplayPort + 12VDC Power Input) FR-1010-17W-4K-DP-USB-24V (DisplayPort + 24VDC Power Input) FR-1010-17W-4K-DP-USB-48V (DisplayPort + 48VDC Power Input) FR-1010-17W-4K-DP-USB-125V (DisplayPort + 125VDC Power Input) FR-1010-17W-4K-DP-USB-250V (DisplayPort + 250VDC Power Input) FR-1010-17W-4K-HDMI-USB (HDMI + Internal 100~240VAC, 50/60Hz) FR-1010-17W-4K-HDMI-USB-12V (HDMI + 12VDC Power Input) FR-1010-17W-4K-HDMI-USB-24V (HDMI + 24VDC Power Input) FR-1010-17W-4K-HDMI-USB-48V (HDMI + 48VDC Power Input) FR-1010-17W-4K-HDMI-USB-125V (HDMI + 125VDC Power Input) FR-1010-17W-4K-HDMI-USB-250V (HDMI + 250VDC Power Input)
Available Models	Standard AC with DisplayPort and HDMI: 19.0"(W) x 1.75"(H) x 18.9"(D) (482.6mm x 44.5mm x 480mm) DC Power: 19.0"(W) x 1.75"(H) x 20.9"(D) (482.6mm x 44.5mm x 530.9mm)
Dimensions	
Warranty	2 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.