

## 17" FULL HD 1080P LCD MONITOR / KEYBOARD 1U RACK DRAWER (DISCONTINUED)



### ***Model: FR-1003-17W-FHD***

- 17.3" Slim 1U Rack LCD / Keyboard / Mouse
- Full HD 1080p, 16:9 Aspect Ratio, Widescreen 1920 x 1080 Max Resolution
  - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
  - Folds down to 1U, 1.75" high
  - Built-in Keyboard & Touch Pad
    - USB connector cable
  - Built-in lockable Slide Rails
- Optional 8 & 16 port KVM, DC Power, HDMI, Audio

***(Important Notice: The FR-1003-17W-FHD model is now end of life and is replaced by the functional equivalent model FR-1010-17W.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

### **Slim 1U All-In-One Full HD 1080p Widescreen Display/Keyboard in a Drawer**

Stealth's 17" Full HD 1080p LCD Monitor / Keyboard 1U Rack Drawer has been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

The model FR-1003-17W-FHD features a widescreen 17.3" Full HD 1080p LCD monitor with 16:9 aspect ratio and comes equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available.

Other FlatRack 1U & 2U Rack Drawer models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

## ADDITIONAL INFORMATION

<b>Construction &amp; Design</b>	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
<b>Screen Size</b>	17.3" (Diagonal)
<b>Type</b>	LCD c/w LED Backlighting
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
<b>Pixel Pitch</b>	0.199mm x 0.199mm
<b>Response Time</b>	40ms Typical
<b>Viewable Image Size</b>	Horizontal: 15.03" / 381.9 mm, Vertical: 8.45" / 214.8 mm
<b>Video Signal</b>	RGB Analog 0.7V Peak to Peak VGA / HD15 (Standard)
<b>Video Input Connectors</b>	DVI-D (Standard) HDMI (Optional)
<b>Viewing Angle</b>	80 (up), 60 (down), 80 (left), 80 (right)
<b>Contrast Ratio</b>	600:1 (typical)
<b>Luminance (Brightness)</b>	400 cd/m2 typical at center (400 Nits)
<b>Controls On-Screen Display</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
<b>Input</b>	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 48 Watts, Standby 5 Watts
<b>Built-in Keyboard / Mouse</b>	104 Keys 2 Button Touch Pad USB cable included
<b>Audio</b>	Optional 2 x 2W Power Speakers with HDMI video input option Optional 3.5mm audio jacks for audio in & out

## Environmental

Operating Relative Humidity (non condensing) 20-90%  
Storage Relative Humidity (non condensing) 5-90%  
Operating Temperature: 0~50C (32~122F)  
Storage Temperature: -5~60C (-23~140F)  
Shock: 10G acceleration (11ms duration)  
Vibration: 5~500Hz 1G RMS random vibration

## Color

Black (standard)

## Unit Weight

Unit Weight: 24 lbs (10.8 Kgs)

## Available Models

FR-1003-17W-FHD – Standard Model

## Additional Options

KVM version with 8 or 16 inputs available  
12/24/48VDC Power supply  
Audio input (3.5mm audio jacks)  
HDMI video input  
3G / HD / SD-SDI Broadcast-grade input

## Dimensions

Standard: 19.0"(W) x 1.75"(H) x 18.1"(D) (482.6mm x 44.5mm x 459.7mm)  
With HDMI/Audio or 3G / HD / SD-SDI options: 19.0"(W) x 1.75"(H) x 20.9"(D) (482.6mm x 44.5mm x 530mm)

## Warranty

2 Year Parts & Labor

## Disclaimer

Note: Specifications are subject to change without notice.