

17" LCD MONITOR / KEYBOARD 1U RACK DRAWER (FR-1010-17)



\$1,300.00 USD

Model: FR-1010-17

- 17" Slim 1U Rack LCD / Keyboard / Mouse
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
 - Built-in Keyboard & Touch Pad
- VGA standard with optional HDMI and DVI-D Ports
 - 17.0" Bright Active Display Area
 - Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, Screen Sizes, Video Inputs
 - Optional 12/24/48/125/250V DC power



GALLERY IMAGES



PRODUCT DESCRIPTION

Optimize your Rack Space with a Slim 1U All-In-One LCD/Keyboard in a Drawer

Stealth's 1U Rack Drawer with built-in Monitor & Keyboard, model FR-1010-17 has been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and touch pad mouse connecting to USB ports. The base model FR-1010-17 features a 17" display supporting 1280 x 1024 resolution and a VGA Video input (HDMI + DVI-D with audio optional).

Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of 12/24/48/125/250VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.264mm x 0.264mm
Response Time	5ms Typical
Viewable Image Size	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA/HD15 Input (standard) HDMI + DVI-D + VGA Inputs (optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 25 Watts, Standby 4 Watts
Built-in Keyboard / Mouse	Dual USB connectors for Keyboard and Mouse 104 Keys 2 Button Touch Pad
Environmental	Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)

Unit Weight

Unit Weight: 26 lbs (12 Kg)

Additional Options

HDMI + DVI-D + VGA with integrated Audio & Dual 2W Speakers

Optional 12/24/48/125/250V DC power

KVM version with 8 or 16 inputs available

KVM (Cat6) version with 8, 16 or 32 inputs available

FR-1010-17-USB (VGA Port + Internal 100~240VAC, 50/60Hz)

FR-1010-17-USB-12V (VGA Port + 12VDC Power Input)

FR-1010-17-USB-24V (VGA Port + 24VDC Power Input)

FR-1010-17-USB-48V (VGA Port + 48VDC Power Input)

FR-1010-17-USB-125V (VGA Port + 125VDC Power Input)

FR-1010-17-USB-250V (VGA Port + 250VDC Power Input)

FR-1010-17-AV4-USB (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + Internal 100~240VAC, 50/60Hz)

Available Models

FR-1010-17-AV4-USB-12V (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + 12VDC Power Input)

FR-1010-17-AV4-USB-24V (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + 24VDC Power Input)

FR-1010-17-AV4-USB-48V (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + 48VDC Power Input)

FR-1010-17-AV4-USB-125V (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + 125VDC Power Input)

FR-1010-17-AV4-USB-250V (DVI-D + VGA + HDMI Inputs c/w Dual 2W Speakers + 250VDC Power Input)

Dimensions

With HDMI + DVI-D and/or DC Power options: 19.0"(W) x 1.75"(H) x 20.9"(D) (482.6mm x 44.5mm x 530mm)

Standard: 19.0"(W) x 1.75"(H) x 18.1 "(D) (482.6mm x 44.5mm x 460mm)

Warranty

2 Year Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.