

17" FULL HD 1080P LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH KVM PORTS (FR-1004-17W-KVM)



\$2,135.00 USD

Model: FR-1004-17W-KVM

- 17.3" Slim 1U Rack LCD / Keyboard / Mouse
- Full HD 1080p, 16:9 Aspect Ratio, Widescreen
1920 x 1080 Max Resolution
- VGA or Cat6 KVM with 8/16 Ports; DVI with 12 Ports
 - Control multiple systems from one LCD
 - Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
 - Built-in QWERTY Keyboard & Touch Pad
- Configurable 12V ~ 480V DC Input, AC Input standard



GALLERY IMAGES



Close up of the Rear View of Cat-6 KVM showing Qty 8 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 16 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 32 RJ45 interface Ports



PRODUCT DESCRIPTION

Manage multiple systems using a Slim Display with Keyboard and Mouse in a single 1U high Rack Drawer!

Stealth's 17.3" Full HD 1080p Series of FlatRacks can support up to 16 individual Workstations or Servers, but require only 1U in height when mounted within a single EIA 19" Rack Cabinet. KVM configurations include 8 or 16 ports with VGA inputs and USB or PS/2 keyboard and mouse connectors. A 12-port model is available for DVI requirements. The optional CAT6 (RJ45) model allows for interfacing to host systems located up to 120 feet or 40 meters away. The flexibility of CAT6 provides support for a variety of video inputs, including VGA, DVI, HDMI and DisplayPort using individual Dongles. Standard models ship with an internal 110/220VAC power supply. Options are available for DC inputs ranging from 12VDC to 480VDC. Design features include locking slide rails that prevent shifting of the FlatRack while open and a molded latching handle that secures the drawer closed when not in use.

Stealth's KVM FlatRacks are available in a range of LCD sizes, including 4:3/5.4 and Widescreen (1080p, 4K). They offer a convenient way for interfacing with multiple systems and are ideal in situations where vertical space is limited. CONTACT US to discuss your needs for a complete solution using any of our custom built 1U to 4U high Rack Mount Servers, along with a FlatRack 1U or 2U KVM.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	17.3" (Diagonal)
Type	LCD c/w LED Backlighting
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.199mm x 0.199mm
Response Time	25ms Typical
Viewable Image Size	Horizontal: 15.03" / 381.9 mm, Vertical: 8.45" / 214.8 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	CAT6: 8 or 16 x RJ45 connectors DVI: 12 x 6' DVI-D and USB Keyboard, Mouse cable sets KVM: 8 or 16 x 6' VGA / HD-15, PS/2 and USB cable sets
Viewing Angle	89 (up), 89 (down), 89 (left), 89 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Power Consumption: Max. 45 Watts, Standby 4 Watts Internal 100~240VAC, 50/60Hz Power Supply
Built-in Keyboard / Mouse	104 Keys 2 Button Touch Pad
Environmental	Operating Temperature: 0~55C (32~131F) Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Storage Temperature: -20~60C (-4~140F) Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Color	Black (standard)

Approvals

UL
UL (Canada)

Unit Weight

Unit Weight: 25.5lbs (11.6 Kgs)

Additional Options

VGA, DVI, HDMI, DisplayPort Dongles (for Cat6 models)

Optional 12/24/48/125/250V DC power

CAT6: 19.0"(W) x 1.75"(H) x 22.83 "(D) (482.6mm x 44.5mm x 580.0mm)

Dimensions

DVI: 19.0"(W) x 1.75"(H) x 22.83 "(D) (482.6mm x 44.5mm x 580.0mm)

KVM8/16: 19.0"(W) x 1.75"(H) x 22.83 "(D) (482.6mm x 44.5mm x 580.0mm)

Warranty

2 Year Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.