

15" OPEN-FRAME LCD MONITOR - SV-1505-OEM



\$995.00 USD

Model: SV-1505-OEM

- 15" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - Optional Resistive or Capacitive Touch
 - Wide Viewing Angles
 - DVI-I, HDMI, DisplayPort video connectors
- UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 Listed
 - FCC, CE, RoHS Compliant
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 15" Open-Frame LCD Monitor is designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive or capacitive touchscreens, or without a front overlay.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 listed.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our industrial LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768 (Auto sync from 800 x 600 to 1024 x 768)
Horizontal Frequency	42.9 ~ 58.8KHz (48.363 KHz typical)
Vertical Frequency	55 - 70Hz (60Hz typical)
Pixel Pitch	0.297mm x 0.297mm
Response Time	16ms Rise (Typical) 7ms Fall (Typical)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	DVI-I VGA via DVI-VGA Adapter (Included) HDMI Displayport
Viewing Angle	88°/88°/88°/88° (Typical)
Contrast Ratio	2000:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Viewable Image Size	Horizontal: 11.97" / 304.1 mm, Vertical: 8.98" / 228.1 mm
Input	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) DC Input: 9V - 36V DC DC Input: 43V - 160V DC DC Input: 180V - 300V DC AC Adapter is Removable
Control Buttons (Rear mounted)	Power, Left, Right, Menu

Controls On-Screen Display	Brightness
	Color
	Image Adjust
	Input Source
	OSD Lockout
	Sound (not applicable)
	Tools
Environmental Rating	N/A – not rated
Environmental	Operating Temperature: -10C – +60C (14F – 140F)
	Storage Temperature: -30C – +85C (-22F – +185F)
	Operating: Relative Humidity 20% ~ 80%
	Storage Relative Humidity: 20% ~ 80%
Panel Finish	N/A – Open-Frame
Unit Weight	Unit Weight: 9.15 Lbs (4.14 Kg)*
	Shipping Weight: 14.85 Lbs (6.72 Kg)*
	* Weight may vary depending on configuration
Dimensions	Add 1.33" (33.78mm) to depth with rear mounted AC Adapter
	With Touch: 15.01" x 11.23" x 2.3" (381.20mm x 285.24mm x 58.38mm) [W x H x D]
	Without Touch: 15.01" x 11.23" x 1.94" (381.20mm x 285.24mm x 49.38mm) [W x H x D]
Approvals	CSA C22.2#62368-1:2019 Ed.3
	UL 62368-1:2019 Ed.3
	RoHS
	CE
Cooling	FCC
	Natural Convection (no fan)

SV-1505-OEM - No Touch Included, 9~36V DC Input, AC Adapter Included

SV-1505-OEM-160V - No Touch Included, 43~160V DC Input

SV-1505-OEM-300V - No Touch Included, 180~300V DC Input

SV-1505-OEM-RT - Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Included

SV-1505-OEM-RT-160V - Resistive Touch (Serial/DB9 and USB), 43~160V DC Input

SV-1505-OEM-RT-300V - Resistive Touch (Serial/DB9 and USB), 180~300V DC Input

SV-1505-OEM-CT-USB - Capacitive Touch (USB), 9~36V DC Input, AC Adapter Included

SV-1505-OEM-CT-USB-160V - Capacitive Touch (USB), 43~160V DC Input

SV-1505-OEM-CT-USB-300V - Capacitive Touch (USB), 180~300V DC Input

Available Models

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.