

19" OPEN-FRAME LCD MONITOR



\$1,295.00 USD

Model: SV-1905-OEM

- 19" OEM/Open-Frame LCD Display
 - Wide DC Input (9-36V DC)
- Wide operating temperature (-10C - +60C)
- Ideal for kiosks, cabinets, walls, panels, and consoles
 - 350 Nits of Brightness, Adjustable Controls
 - DVI-I, HDMI & DisplayPort video connectors
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

The SV-1905-OEM is Stealth's most recent introduction of an Open-Frame LCD Display designed specifically for cabinet, console, kiosk or other applications which do not require our Panel Mount version. This versatile display mounts from within the enclosure providing a wide array of options to ensure the end product meets your design needs. Built from solid cold rolled steel, it is designed for wide temperature operation and includes both an AC and DC input.

The SV-1905-OEM is backed with an impressive 3-year warranty. It delivers on performance! An optional resistive or capacitive touch screen permits this product to replace traditional mice and allows users to directly interact with any system. View our other OEM/Open Frame LCD Displays if you need an alternate size.

As with all Stealth products, the unit is built in-house with our rigorous processes which both meet and exceed the ISO 9001 Quality Management System. Our attention to detail, multiple quality check points ensures the final product will arrive and operate the first time.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	19.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.294mm x 0.294mm
Response Time	10ms (Typical, On/Off)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	DVI-I c/w DVI to VGA Adapter HDMI Displayport
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm
Input	90 ~ 264V AC, 47~63Hz rear-mounted (removable) Power Supply DC Input (std.): 9V - 36V DC DC Input (opt.): 43V - 160V DC DC Input (opt.): 180V - 300V DC
Control Buttons (Rear mounted)	Power, Left, Right, Menu
Controls On-Screen Display	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
Environmental Rating	N/A - not rated
Environmental	Operating Temperature: -10C - +60C (14F - 140F) Storage Temperature: -30C - +85C (-22F - +185F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
Cooling	Natural Convection (no fan)

Panel Finish	N/A – Open-Frame
Unit Weight	Unit Weight: 9.15 Lbs (4.14 Kg)* Shipping Weight: 14.85 Lbs (6.72 Kg)* * Weight may vary depending on configuration
Dimensions	17.8"(w) x 14.05"(h) x 3.45"(d) (452.12mm x 356.74mm x 87.64mm) NOTE: The depth does not include touch glass, add 12mm to depth for any touch option Without Mounted Power Supply: 17.8" (w) x 14.05" (h) x 2.11" (d) (452.12mm x 356.74mm x 53.72mm)
Available Models	SV-1905-OEM – No Touch Included SV-1905-OEM-160V – (43V – 160V DC) SV-1905-OEM-300V – (180V – 300V DC) SV-1905-OEM-CT-DB9 – Capacitive Touch (Serial/DB9) SV-1905-OEM-CT-USB – Capacitive Touch (USB) SV-1905-OEM-CT-USB-160V – Capacitive Touch & 43V – 160V DC SV-1905-OEM-CT-USB-300V – Capacitive Touch & 180V – 300V DC SV-1905-OEM-RT – Resistive Touch (Serial/DB9 and USB) SV-1905-OEM-RT-160V – Resistive Touch & 43V – 160V DC SV-1905-OEM-RT-300V – Resistive Touch & 180V – 300V DC
Warranty	3 Year Parts and Labor
Disclaimer	Note: Specifications are subject to change without notice.