

21.5" OPEN-FRAME LCD MONITOR





\$1,045.00 USD

Model: SV-2150WS-OEM

- 21.5" OEM/Open-Frame Widescreen LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - Optional Touch Screen (Resistive)
 - 16:9 Aspect Ratio
 - 1920 x 1080 Maximum Resolution
 - 250 Nits of Brightness, Adjustable Controls
- VGA, DVI-D, Displayport & HDMI connectors
 - Wide Viewing Angles, 178°
 - cULus Listed
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 21.5" Open-Frame LCD is an OEM widescreen monitor that easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting the display is accomplished by simply securing the screw holes located in the side flanges of the LCD.

The SV-2150WS-OEM LCD is available with optional resistive touchscreen, or without a front overlay whatsoever.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our Rugged LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	21.5" (Diagonal)
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Horizontal Frequency	31.5 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.25mm x 0.25mm
Response Time	6ms Typical
Type	IPS LCD Panel c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI Displayport
Viewing Angle	178° / 178° (H / V) - (Viewing angle of LCD panel sans touch)
Contrast Ratio	1000:1 (typical) 25000:1 (dynamic)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 18.85" / 478.79 mm, Vertical: 10.68" / 271.27 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync: TTL Level (Positive/Negative) Composite Sync on Green: (0.3Vp-p negative 0.7Vp-p positive) Composite Sync: TTL Level (Positive/Negative)
Environmental Rating	OEM/Open-Frame chassis - not rated
Environmental	Operating Temperature: 0 - 40C (32 to 104 F) Storage Temperature: -10 - 60C (14 to 140 F) Operating: Humidity 20% ~ 80%, non-condensing Storage Humidity: 10% to 85%, non-condensing

Approvals	cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07
Input	AC Input: 100 - 240VAC ~ 50-60Hz, 1.3A
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Menu/Exit Reset/Eco, Input/Select, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Panel Finish	N/A - Open-Frame
Unit Weight	10.25 lbs / 4.66 kg
Dimensions	20.92"(W) x 12.614"(D) x 2.21"(H) (531.36mm x 320.39mm x 56.13mm)
Available Models	SV-2150WS-OEM - Open Frame Only (no touch) SV-2150WS-OEM-RT - Resistive (USB and Serial / DB9)
Warranty	3 Year Parts and Labor
Disclaimer	Note: Specifications are subject to change without notice.