


24" OPEN-FRAME LCD MONITOR (SV-2410W-OEM)



\$1,295.00 USD

Model: SV-2410W-OEM

- 24" OEM/Open-Frame Widescreen LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - Optional Touch Screen (Capacitive or Resistive)
 - 16:10 Aspect Ratio
 - 1920 x 1200 Native Resolution
 - 300 Nits of Brightness, Adjustable Controls
- VGA, DVI-D, Displayport & HDMI connectors
 - Wide Viewing Angles, 178°
 - 3 Year Warranty



PRODUCT DESCRIPTION

Stealth's 24" Open-Frame LCD is an OEM widescreen monitor that easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting the display is accomplished by simply securing the screw holes located in the side flanges of the LCD.

The SV-2410W-OEM LCD is available with capacitive or resistive touchscreen, or without a front overlay whatsoever.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our Rugged LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	24.0" (Diagonal)
Aspect Ratio	16:10
Native Resolution	1920 x 1200 (Auto sync from 640 x 480 to 1920 x 1200)
Horizontal Frequency	31.5KHz - 95KHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.27mm x 0.27mm
Response Time	5ms Typical
Type	IPS LCD Panel c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI Displayport DisplayPort Multi-Stream Transport (MST) port (Clone or Extended Desktop)
Viewing Angle	178° / 178° (H / V) - (Viewing angle of LCD panel sans touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Viewable Image Size	Horizontal: 20.41" (518.4mm) Vertical: 12.76" (324.0mm)
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync Sync on Green Composite Sync
Input	AC Input: 120 - 240VAC ~ 60/50 Hz Power Consumption: 29 W (typical)
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF

Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	OEM/Open-Frame chassis – not rated
Environmental	Operating Altitude: 0 – 16,404 feet (0 – 5000m) Operating Humidity: 20% – 80% Operating Temperature: 5C – 35C (41F – 95F) Storage Altitude: 0 – 40,000 Feet (0 – 12,192m) Storage Humidity: 10% – 85% Storage Temperature: -10C – 60C (14F – 140F)
Panel Finish	N/A – Open-Frame
Unit Weight	20 Pounds (9.07Kg)
Dimensions	OEM With Touch: 23.04"W x 15.33"H x 2.8"D OEM Without touch: 23.04"W x 15.33"H x 2.5"D SV-2410W-OEM – Open-Frame Only (No Touch) SV-2410W-OEM-CT-DB9 – Capacitive (Serial / DB9) SV-2410W-OEM-CT-USB – Capacitive (USB) SV-2410W-OEM-RT – Resistive (USB and Serial / DB9)
Available Models	
Warranty	3 Year Parts and Labor
Disclaimer	Note: Specifications are subject to change without notice.