

17" OPEN-FRAME LCD MONITOR (SV-1701-OEM - DISCONTINUED)




Model: SV-1701-OEM

- 17" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - Touch Screen Optional (Capacitive or Resistive)
 - Wide Viewing Angles
 - 250 Nits of Brightness, Adjustable Controls
 - VGA & DVI-D video connectors
 - cULus Listed
 - 1 Year Warranty

(Important Notice: The SV-1701-OEM model is now end of life and is replaced by the functional equivalent model SV-1705-OEM.)



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 17" Open-Frame LCD Monitor is designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive/capacitive touchscreens or without a front overlay.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our Rugged LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	17.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.264mm x 0.264mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	170° (H) / 160° (V) – (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical) SmartContrast: 20,000,000:1
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 13.39" / 340.1 mm, Vertical: 10.71" / 272.03 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync Sync on Green
Input	AC Input: 100-240V, 50-60Hz, 1.5A
Control Buttons (Rear mounted)	Smart Image, Down, Up, Menu/OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	OEM/Open-Frame chassis – not rated

Approvals	cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07
Panel Finish	N/A - Open-Frame
Unit Weight	Unit Weight: 7.5 Lbs (3.4 Kg)* Shipping Weight: 13.8 Lbs (6.26 Kg)* * Weight may vary depending on configuration
Dimensions	For Dimensions please refer to the OEM Dimensional Drawing SV-1701-OEM - No protective glass, LCD directly exposed SV-1701-OEM-RT - Resistive Touch with Serial/DB9 and USB Interface SV-1701-OEM-CT-SERIAL - Capacitive Touch with Serial/DB9 Interface SV-1701-OEM-CT-USB - Capacitive Touch Screen with USB interface
Available Models	
Warranty	1 Year Parts & Labor 1 Year Extended Warranty available (see Configurator/Price List)
Disclaimer	Note: Specifications are subject to change without notice.