


17" PANEL MOUNT LCD MONITOR (SV-1705-PM)





\$1,600.00 USD

Model: SV-1705-PM

- Panel Mount LCD, 17" Industrial Grade
- NEMA 4/4X / IP66 Environmentally Sealed
- Touch Screen Standard (Capacitive or Resistive)
 - Wide Viewing Angles
- 350 Nits of Brightness, Adjustable Controls
- Stainless Steel (NEMA 4X/IP66) & Custom painted bezel options
 - DVI-I, HDMI & DisplayPort video connectors
- UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 Listed
 - FCC, CE, RoHS Compliant
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 17" Panel Mount LCD Monitor designed for industrial and commercial applications comes equipped with an environmentally sealed front panel that is resistant to splashes or hose downs. All Stealth Panel Mount LCD products are easily installed by securing the rear studs into your console, panel or wall.

Stealth's 17" Industrial Panel Mount Display is environmentally sealed to NEMA 4/4X / IP66 and are ideal for applications where dirt, dust, moisture and water are present. Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being CE, FCC, *UL 62368-1:2019 Ed.3* & CSA C22.2#62368-1:2019 Ed.

Stealth's Rugged LCD Displays are constructed from solid steel and stainless steel for corrosion resistance applications. We offer Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 15" up to 24" diagonal sizes. Our LCDs are available with various Touch Screen options including Resistive or Capacitive. For non-touch applications our anti-glare protective glass overlay is installed for maximum protection.

ADDITIONAL INFORMATION

Bezel Type	Panel Mount
Screen Size	17.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Horizontal Frequency	42.9 ~ 58.8KHz (48.363 KHz typical)
Vertical Frequency	55 - 70Hz (60Hz typical)
Pixel Pitch	0.264mm x 0.264mm
Response Time	20ms Rise (Typical), 10ms Fall (Typical)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	DVI-I c/w DVI to VGA Adapter HDMI Displayport
Viewing Angle	80°/80°/60°/80° (Typical)
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 13.30" / 337.92 mm, Vertical: 10.64" / 270.336 mm
Input	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) DC Input: 9V - 36V DC DC Input: 43V - 160V DC DC Input: 180V - 300V DC AC Adapter is Removable
Control Buttons (Rear mounted)	Power, Left, Right, Menu

	Brightness
	Color
	Image Adjust
Controls On-Screen Display	Input Source
	OSD Lockout
	Sound (not applicable)
	Tools
	Standard Bezel: NEMA 4/4X / IP66 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water
Environmental Rating	Optional Stainless Steel Bezel: NEMA 4X / IP66 Front Panel (when properly installed) corrosion protection, protection against windblown dust and rain, splashing water, and hose-directed water
	Operating Temperature: -10C - +60C (14F - 140F)
Environmental	Storage Temperature: -30C - +85C (-22F - +185F)
	Operating: Relative Humidity 20% ~ 80%
	Storage Relative Humidity: 20% ~ 80%
Panel Finish	Black Baked Enamel (Standard)
	Stainless Steel - Brushed #304 (Optional)
Unit Weight	Unit Weight: 14.9 Lbs (6.76 Kg)*
	* Weight may vary depending on configuration
Dimensions	Add 1.33" (33.78mm) to depth with rear mounted AC Adapter
	Panel Mount: 18.9"(W) x 17.0"(H) x 2.5"(D) 480.06mm x 431.8mm x 63.68mm
	CSA C22.2#62368-1:2019 Ed.3
Approvals	UL 62368-1:2019 Ed.3
	RoHS
	CE
	FCC
Cooling	Natural Convection (no fan)

SV-1705-PM-RT – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Include

SV-1705-PM-RT-160V – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 43~160V DC Input

SV-1705-PM-RT-300V – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 180~300V DC Input

SV-1705-PM-CT-USB – Painted Bezel, Capacitive Touch (USB), 9~36V DC Input, AC Adapter Included

SV-1705-PM-CT-USB-160V – Painted Bezel, Capacitive Touch (USB), 43~160V DC Input

SV-1705-PM-CT-USB-300V – Painted Bezel, Capacitive Touch (USB), 180~300V DC Input

SV-1705-PM-RT-SS – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Included

SV-1705-PM-RT-SS-160V – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 43~160V DC Input

SV-1705-PM-RT-SS-300V – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 180~300V DC Input

SV-1705-PM-CT-SS-USB – Stainless Steel Bezel, Capacitive Touch (USB), 9~36V DC Input, AC Adapter Included

SV-1705-PM-CT-SS-USB-160V – Stainless Steel Bezel, Capacitive Touch (USB), 43~160V DC Input

SV-1705-PM-CT-SS-USB-300V – Stainless Steel Bezel, Capacitive Touch (USB), 180~300V DC Input

Available Models

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.