

21.5" RACK MOUNT LCD MONITOR (SV-2155W-RM)



\$1,295.00 USD

Model: SV-2155W-RM

- 21.5" Wide Screen Rack Mount LCD
- Full 1080p HD resolution (1920 x 1080)
- VGA and DVI-D Inputs (Optional HDMI & Displayport)
 - Installs into (8U) of rack space
 - Easy snap in/out installation
- Optional Resistive, Capacitive or PCAP Multitouch Touch Screen
 - Front-access OSD Controls
 - 2 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model SV-2155W-RM is our widescreen 21.5" Rack Mount LCD which installs into industry standard 19" EIA rack cabinets and enclosures in minutes. The SV-2155W-RM features a Full HD 1080p display (1920 x 1080 resolution), 16:9 Aspect Ratio with VGA and DVI-D video inputs standard. The optional AV4 upgrade provides HDMI & Display Port video connections, along with integrated Audio and dual 2 Watt Speakers. The 21.5" Rack display can also be configured with a Resistive, Capacitive or PCAP Multitouch Touch Screen and DC power options including 12V, 24V, 48V, 125V and 250V DC.

Stealth builds high quality Rackmount LCD monitors suited for industrial and commercial applications. We offer a wide range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Rack Mount
Screen Size	21.5" (Diagonal)
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.248mm x 0.248mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA/HD15 + DVI-D Inputs (standard) VGA/HD15 + HDMI + DisplayPort with Audio In/Out, Dual 2W Speakers (optional)
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 18.77" / 476.64mm, Vertical: 10.56" / 268.11mm Optional: 12V, 24V, 48V, 125V and 250V DC with Terminal Block
Input	Power Consumption: 32W Max, Standby 4W 12VDC input at LCD, Rear mounted AC power supply included, AC Input: 100-240VAC 60/50 Hz @ 0.7A
Audio	Available only with AV4 Option Includes: 2 x 2W Speakers with 3.5mm Audio Jack
Control Buttons (Rear mounted)	Smart Image, Down, Up, Menu/OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	N/A - not rated

Environmental	Non-Operating Altitude: 40,000 ft
	Operating Altitude: 16,000 ft
	Operating Humidity: 20~90%, non-condensing
	Storage Humidity: 5~90%, non-condensing
	Vibration: 10-300Hz 0.5G RMS random vibration
	Operating Temperature: 0~55C (32~131F)
	Storage Temperature: -20~60C (-4~140F)
Panel Finish	Shock: 10G acceleration (11ms duration)
	Black Front Panel Finish
Unit Weight	Unit Weight: 19.4lbs / 8.8 kg
LCD Mounting Options	Rear VESA 100mm Mounting
	Installs into (8U) of rack space
	Designed to fit standard 19" EIA Racks
Dimensions	Rack Mount: 19.75"(W) x 13.89"(H) x 2.53"(D) (501.9mm x 353mm x 64.4mm)
	SV-2155W-RM – Standard Model with VGA/HD15 and DVI inputs
Available Models	SV-2155W-RM-AV4 – incl. VGA/HD15, HDMI, DisplayPort with Audio In/Out, Dual 2W Speakers
	SV-2155W-RM Options:
	-RTe-USB (Resistive Touchscreen with USB interface)
	-CT-USB (Capacitive Touchscreen with USB interface)
	-PCT-USB (Projective Capacitive Multitouch Touchscreen, 10-points, with USB interface)
	-12V (9~18VDC input)
	-24V (18~36VDC input)
	-48V (36~75VDC input)
Warranty	-125V (125VDC input)
	-250V (180~425VDC input)
Disclaimer	2 Year Parts & Labor
	Note: Specifications are subject to change without notice.