

## 17" SUNLIGHT READABLE OPEN-FRAME LCD MONITOR



**\$1,230.00 USD**

***Model: SV-1700LED-OEM-HB***

- 17.0" Sunlight Readable OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
  - 1,000 Nits (Cd/m2) HIGH BRIGHTNESS
    - LED Backlighting
    - Adjustable Brightness Controls
- Touchscreen Optional (Resistive or Capacitive)
  - High Shock & Vibration
  - Low Power Consumption
- Remote Brightness Control Option
- Digital controls w/on screen display
- Also available in Panelmount Design





## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth.com's 17" Sunlight Readable Open-Frame LCD Monitor is designed to operate in extreme ambient light conditions. Stealth high bright monitors outperform commercially available products that wash out in direct and indirect sunlight conditions.

This 17" Sunlight Readable Open-Frame Display is rated for 1,000 Nits (Cd/m<sup>2</sup>) high brightness and comes equipped with adjustable brightness controls. The display can also be configured with Resistive or Capacitive touchscreen. Ideal for inside and outside use in marine, mobile, kiosks, control, security, drilling platforms, outdoor displays, yachts, aircraft or digital sign applications.

Stealth.com has a wide range of industrial LCD products that include; NEMA 4/4X / IP65 Stainless Steel, Panel Mount, Rackmount, Open Frame and custom designed configurations.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Open-Frame
<b>Screen Size</b>	17.0" (Diagonal)
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Pixel Pitch</b>	0.294mm x 0.294mm
<b>Response Time</b>	5ms Typical
<b>Type</b>	LCD c/w LED Backlighting
<b>Video Input Connectors</b>	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
<b>Viewing Angle</b>	80 (up), 80 (down), 80 (left), 80 (right) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	1000:1 (typical)
<b>Luminance (Brightness)</b>	1000 cd/m2 typical at center (1000 Nits)
<b>Viewable Image Size</b>	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
<b>Video Signal</b>	ANALOG: 0.7 Vp-p/75 Ohms
<b>Sync Signal</b>	Separate Sync Sync on Green Composite Sync (Positive/Negative)
<b>Input</b>	Universal Power Supply (removable) 90-240V, +12VDC@100W
<b>Control Buttons (Rear mounted)</b>	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
<b>Controls On-Screen Display</b>	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
<b>Environmental Rating</b>	OEM/Open-Frame chassis - not rated
<b>Panel Finish</b>	N/A - Open-Frame

**Unit Weight**

Unit Weight: 18 Lbs (8.16Kg)

**Available Models**

SV-1700LED-OEM-RT-HB-SERIAL – Resistive Touch with Serial/DB9 Interface

SV-1700LED-OEM-RT-HB-USB – Resistive Touch with USB Interface

SV-1700LED-OEM-CT-HB-SERIAL – Capacitive Touch with Serial/DB9 Interface

SV-1700LED-OEM-CT-HB-USB – Capacitive Touch with USB Interface

**Dimensions**

For Dimensions please refer to the OEM Dimensional Drawing

**Warranty**

1 Year Parts & Labor

**Disclaimer**

Note: Specifications are subject to change without notice.