

18.5" ZERO BEZEL PANEL MOUNT LCD WIDESCREEN DISPLAY SVZ-1850W



\$865.00 USD

Model: SVZ-1850W-PM-PCT

- Sealed Front Panel Design to NEMA 4/IP65
- 10-point Multi-Touch (PCT / PCAP) Touchscreen
 - 7H Hardness Anti-Scratch Surface
- HDMI/DVI-D/VGA video connectors
 - 1366 x 768 Native Resolution
 - 16:9 Aspect Ratio
 - Panel or VESA Mount



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 18.5" Zero Bezel Panel Mount LCD Widescreen Display with multi-touch PCAP Touchscreen features a zero bezel, edge to edge design that eliminates dust and debris build-up at the edge and corners of the display.

Stealth's Zero Bezel Display is equipped with an environmentally sealed NEMA 4/IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. The Stealth model SVZ-1850W-PM-PCT with Panel or VESA mounting easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications.

The Zero Bezel LCD series utilizes Projected Capacitive touchscreen technology (PCAP) allowing for a modern user interface thereby making use of new and extended ways of user input and control and allows for up to 10 touch points. Gesture-based interactions by touching and pointing, with one finger or more, rotate, pinch to zoom and move objects on the display.

From the industrial factory floor to the stock market floor, this unit provides the touchscreen capabilities necessary for multiple fast-paced environments.

Stealth offers a wide range of Rugged LCD displays offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products yet customizable in 15" up to 24" diagonal sizes.

ADDITIONAL INFORMATION

Bezel Type	Zero Bezel Panel Mount VESA
Screen Size	18.5" Diagonal
Aspect Ratio	16:9
Native Resolution	1366 x 768
Luminance (Brightness)	400 cd/m2 typical at center (400 Nits)
Contrast Ratio	1000:1 (typical)
Viewing Angle	170° / 160° (H / V)
Video Input Connectors	DVI-D VGA / HD-15 HDMI
Touchscreen Interface	10-point Projected Capacitive (PCAP) Surface Hardness: 7H Hardness Anti-Scratch Surface
Audio	10W Stereo Speakers
Unit Weight	Unit Weight: 14.33 lb (6.5 kg)
Dimensions	18.51" x 11.63" x 2.13" (470.25 x 295.38 x 54 mm)
Panel Finish	Zero Bezel Design
Housing	Aluminum
Mounting	Panel Mount VESA Mount (75 x 75mm, 100 x 100mm)
Power Input	9-36VDC Input, includes external AC adapter
Power Supply	100 – 240V AC Input, 120W 24V DC 5A Output
Environmental Rating	NEMA 4, IP65 Front panel

Shock: IEC 60068-2-27, 20G, Half-sine, 11ms
Vibration: IEC 60068-2-64, Non-operation : 10Hz to 200Hz, 1.5Grms,
X, Y, Z, 30 mins each Axis
Operating Temperature: 0~50C (32~122F)
Storage Temperature: -20~60C (-4~140F)
Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-
Operating)

RoHS

CE

FCC

SVZ-1850W-PM-PCT – Multi-Touch (PCT / PCAP) Touchscreen

1 Year Parts & Labor

Note: Specifications are subject to change without notice.

Environmental

Approvals

Available Models

Warranty

Disclaimer