

## 24" ZERO BEZEL PANEL MOUNT LCD WIDESCREEN DISPLAY



**\$995.00 USD**

***Model: SVZ-2400W-PM-PCT***

- Sealed Front Panel Design to NEMA 4/IP65
- 10-point Multi-Touch (PCT / PCAP) Touchscreen
  - 7H Hardness Anti-Scratch Surface
  - HDMI/DVI-D/VGA video connectors
- Full HD 1080p, 1920 x 1080 Maximum Resolution
  - 16:9 Aspect Ratio
  - Panel or VESA Mount



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's 24" Zero Bezel Panel Mount LCD Widescreen Display with multi-touch PCAP Touchscreen features a zero bezel, edge to edge design that eliminates dust and debris build-up at the edge and corners of the display.

Stealth's Zero Bezel Display is equipped with an environmentally sealed NEMA 4/IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. The Stealth model SVZ-2400W-PM-PCT with Panel or VESA mounting easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications.

The Zero Bezel LCD series utilizes Projected Capacitive touchscreen technology (PCAP) allowing for a modern user interface thereby making use of new and extended ways of user input and control and allows for up to 10 touch points. Gesture-based interactions by touching and pointing, with one finger or more, rotate, pinch to zoom and move objects on the display.

From the industrial factory floor to the stock market floor, this unit provides the touchscreen capabilities necessary for multiple fast-paced environments.

Stealth offers a wide range of Rugged LCD displays offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products yet customizable in 15" up to 24" diagonal sizes.

## ADDITIONAL INFORMATION

<b>Bezel Type</b>	Zero Bezel Panel Mount VESA
<b>Screen Size</b>	24.0" (Diagonal)
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
<b>Luminance (Brightness)</b>	250 cd/m2 typical at center (250 Nits)
<b>Contrast Ratio</b>	3000:1 (typical)
<b>Viewing Angle</b>	170° (H), 170° (V) - Typical
<b>Video Input Connectors</b>	DVI-D VGA / HD-15 HDMI
<b>Touchscreen Interface</b>	10-point Projected Capacitive (PCAP) Surface Hardness: 7H Hardness Anti-Scratch Surface
<b>Audio</b>	10W Stereo Speakers
<b>Unit Weight</b>	Unit Weight: 14.33 lb (6.5 kg)
<b>Dimensions</b>	22.71" x 13.62" x 2.13" (576.9 x 345.9 x 54 mm)
<b>Panel Finish</b>	Zero Bezel Design
<b>Housing</b>	Aluminum
<b>Mounting</b>	Panel Mount VESA Mount (75 x 75mm, 100 x 100mm)
<b>Power Input</b>	9-36VDC Input, includes external AC adapter
<b>Power Supply</b>	100 - 240V AC Input, 120W 24V DC 5A Output
<b>Environmental Rating</b>	NEMA 4, IP65 Front panel

## Environmental

Shock: IEC 60068-2-27, 20G, Half-sine, 11ms  
Vibration: IEC 60068-2-64, Non-operation : 10Hz to 200Hz, 1.5Grms, X, Y, Z, 30 mins each Axis  
Operating Temperature: 0~50C (32~122F)  
Storage Temperature: -20~60C (-4~140F)  
Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating)

## Approvals

RoHS  
CE  
FCC

## Available Models

SVZ-2400W-PM-PCT – Multi-Touch (PCT / PCAP) Touchscreen

## Warranty

1 Year Parts & Labor

## Disclaimer

Note: Specifications are subject to change without notice.