

Model: LPC-350M Mobile Small Form Factor PC
Featuring Intel's Intel Pentium M and Celeron M Processors

Small, Rugged, Full featured PC

The LPC-350 delivers the utilizes Intel's Pentium and Celeron M series processors, designed for optimum power efficiency. The rugged all aluminum small form factor chassis measures about the size of a hard cover novel yet surpasses performance of most desktops and notebook PCs.



Stealth is recognized world-wide as a leading supplier of small form factor computers. For unsurpassed performance and reliability contact Stealth today to discuss your application requirements.

Model: LPC-350M - Mobile Mini PC

Features:



(click on images for larger pictures)

- **Car start delay timer** (delay the pc start time)
- **Key removed delay time** (delay the pc shutdown)
- **Hardware shutdown** (shutdown the PC when the operating system was unable to perform the shutdown)
- Powerful Intel Pentium M and Celeron M Processors
- Small Size for Easy Deployment
- 12 VDC Operation, ideal for mobile/field
- Intel Graphics Media Accelerator 950
- 3D Graphics with 16x9 Capability
- Built-in Gigabit LAN, USB 2.0, 1394a Firewire, Audio, Serial, Video
- Low Profile Rugged Aluminum Chassis
- Slim Slot Loading Optical Drives
- Solid State Hard Drives (SSD) optional
- Windows Vista & XP Pro Compatible, **other O/S Options Available*
- **Dimensions:**
5.8" (W) x 10.0" (D) x 1.65" (H)
(14.7 x 25.4 x 4.2 cm)



LPC-350M Specifications

- **Processor**
Intel Celeron M370 (1.5GHz) (Standard offering)
or Intel Pentium M740 (1.73GHz)
- **Chipset**
 - Mobile Intel 82915GM/GMS/910 GML
 - Memory Controller: Mobile 82915GM/GMS/82910GML
 - IO Controller: Intel 82801FBM I/O Controller Hub ICH6M
 - Integrated IEEE 1394a Agere FW232 Firewire chipset
- **BIOS**
4MB Award PnP Flash BIOS
- **Memory**
 - 1 DDR2 SO-Dimm memory slots providing options from 512MB (Standard offering) to 2GB's (MAX) of RAM
- **Internal Storage**
 - Offered with 80GB (Standard offering), 120 and 320GB SATA, 2.5" Hard Drive
 - SSD (Solid State Drives) optional
- **Optical Drives**
 - Slim Slot Load DVD-Rom/CD-RW (Standard offering)
 - Optional upgrade to a Slot Load DVDRW/CD-RW
- **Video** (Video Resolutions Supported)
 - Onboard Mobile Intel 82915GM/GMS, 910GML Express Chipset Family
 - Shared 128MB Video Memory
- **Ethernet Port**
 - Integrated 10/100 Base-T Intel Pro/100 VE Desktop Adapter, RJ45 connection
- **Audio**
 - Integrated Realtek Software AC 97 Audio CODEC
- **Mobile PC Features**
 - Car start delay timer** (delay the pc start time)
 - Key removed delay time** (delay the pc shutdown)
 - Hardware shutdown** (shutdown the PC when the operating system was unable to perform the shutdown)
- **Operating Systems**
 - Windows VISTA, Windows XP Pro
 - *Optional: Linux, QNX & embedded.
- **Power Management**
 - ACPI 1.0b compliant
 - Direct power management
 - Wake-on event
- **Hardware Monitor**
 - Processor temperature
 - Voltage
- **Chassis Description**
 - Low Profile Rugged Aluminum Chassis
- **Power Input**
 - Rear 12VDC power Jack ideal for mobile applications.
 - Input is 12VDC +/-5% @ 7A (84W)
 - Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz
- **Options**
 - Solid State Drives (SSD) SATA
 - Wall Mount Bracket
 - USB Key (mini-Flash drive) for easy file transfer
 - Remote power option Ideal for OEM or Cabinet manufacturers
 - Dual Video Option is Available (Contact Stealth for further information)
- **Rear Panel** (Click here for layout)
 - 2 x RS232 COM port
 - 2 PS/2 ports for Keyboard & Mouse
 - Fast Ethernet RJ45 Network connection
 - Audio Line-Out Jack
 - 2 x USB 2.0 Ports
 - Digital Video Interface (DVI-I)
 - 12VDC Power Input Jack
- **Front Panel** (Click here for layout)
 - IEEE 1394a Firewire port
 - 1 x USB 2.0 Port
 - Microphone Input Jack
 - Headphone output Jack
 - Power-on button
 - Reset button
 - Power and Hard Drive notification LED
- **Dimensions**
 - 5.8" (W) x 10.0" (D) x 1.65" (H)
(14.7 x 25.4 x 4.2 cm)
- **Environmental**
 - Operating Temperature: 0-40C
 - Non-Operating Temperature: (Storage) -20~60C
 - Operating RH (non condensing) 10-80%
 - Non Operating RH (non condensing) 0-90%
- **Shipping Weight**
 - < 10.0 lbs. (4.5kg) (Depending on configuration)
- **Warranty**
 - 1 Year

Note: Specifications are subject to change without notice.
All other trademarks and copyrights are the property of their respective owners.