

Model: LPC-450G3 Duo Core Small Form Factor PC with Multi Gigabit LAN *Featuring Intel's Core 2 Duo Technology*

Simply Amazing! ... 4 Gigabit Ethernet LAN/WAN ports in a powerful small computer

Stealth's tiny PC has a total of 4 GB Ethernet ports available for unprecedented connectivity in a small form PC (3 front & 1 Rear access) The LPC-450G3 is built utilizing Intel's blazing speed Core 2 Duo processors delivering the ultimate in small form factor performance. Ideal applications include but not limited to; security, VPN applications, network appliance, bandwidth controller, network diagnostics, mini servers and any application that would require a small sized PC to operate in tight space environments.



Stealth Computer is recognized world-wide as a leading supplier of small form factor computers. For unsurpassed performance and reliability contact Stealth Computer today to discuss your application requirements.

Model: LPC-450G3 - Dual Core Mini PC with Multi Gigabit LAN

Features:




- **Powerful Intel Core 2 Duo Processors**
- **4 Gigabit Ethernet LAN/WAN ports**
- Small Size for Easy Deployment
- 12 VDC Operation, ideal for mobile/field
- Intel Graphics Media Accelerator 950
- 3D Graphics with 16x9 Capability
- Built-in Gigabit LAN, USB 2.0, 1394a Firewire, Audio, Serial, Video
- Low Profile Rugged Aluminum Chassis
- Slim Slot Loading Optical Drives
- Solid State Hard Drives (SSD) optional
- Windows Vista & XP Pro Compatible, **other O/S Options Available*
- **Dimensions:**
5.7"(W) x 9.9"(D) x 1.65"(H)
(14.6 x 25 x 4.2 cm)

(click on images for larger pictures)



LPC-450G3 Specifications

- **Processor**
Supports Intel's Dual Core Processors using Intel's Core 2 Duo Technology, offered with Intel's T5500 (1.66Ghz) (Standard offering), T7400 (2.16Ghz) and T7600 (2.33Ghz)
- **Chipset**
 - Intel's 945GM Northbridge
 - Intel's ICH7M Southbridge
 - Integrated IEEE 1394a Agere FW232 Firewire chipset
- **BIOS**
4MB Award PnP Flash BIOS
- **Memory**
 - 1 DDR2 SO-Dimm memory slots providing options from 1GB (Standard offering) to 2GB's (MAX) of RAM
- **Internal Storage**
 - Offered with 160GB (Standard offering), Optional: 250-500GB SATA, 2.5" Hard Drives
 - SSD (Solid State Drives) optional
- **Optical Drives**
 - Slim Slot Load DVD-Rom/CD-RW (Standard offering)
 - Optional upgrade to a Slot Load DVDRW/CD-RW
- **Video** (Video Resolutions Supported)
 - Onboard Intel Graphics Media Accelerator 950
 - Shared 128MB Video Memory
- **Ethernet Port**
 - 3x - Front - Gigabit Agere PCIe ET1310 Ethernet controllers 10/100/1000
 - 1x - Rear - Gigabit Agere PCIe ET1310 Ethernet controllers 10/100/1000
- **Audio**
 - Integrated Realtek Software AC 97 Audio CODEC
- **Operating Systems**
 - Windows VISTA, Windows XP Pro
 - *Optional: Linux, QNX & embedded.
- **Power Management**
 - ACPI 1.0b compliant
 - Direct power management
 - Wake-on event
- **Hardware Monitor**
 - Processor temperature
 - Voltage

- **Chassis Description**
 - Low Profile Rugged Aluminum Chassis
 - **Power Input**
 - Rear 12VDC power Jack ideal for mobile applications.
 - Input is 12VDC +/-5% @ 7A (84W)
 - Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz
- Volts DC Input**
- 
- **Options**
 - Solid State Drives (SSD) SATA
 - Wall Mount Bracket
 - USB Key (mini-Flash drive) for easy file transfer
 - Remote power option Ideal for OEM or Cabinet manufacturers
 - **Rear Panel** (Click here for layout)
 - 2 x RS232 COM port
 - 2 PS/2 ports for Keyboard & Mouse
 - 1x - Rear - Gigabit Agere PCIe ET1310 Ethernet controllers 10/100/1000
 - Audio Line-Out Jack
 - 2 x USB 2.0 Ports
 - DVI-I connector (includes DVI to VGA adapter)
 - 12VDC Power Input Jack
 - **Front Panel** (Click here for layout)
 - 3x - Front - Gigabit Agere PCIe ET1310 Ethernet controllers 10/100/1000
 - IEEE 1394a Firewire port
 - 1 x USB 2.0 Port
 - Microphone Input Jack
 - Power-on button
 - **Dimensions**
 - 5.7"(W) x 9.9"(D) x 1.65"(H)
 - (14.6 x 25 x 4.2 cm)
 - Chassis sectional drawing (PDF)
 - **Environmental**
 - Operating Temperature: 0-40C
 - Non-Operating Temperature: (Storage) -20~60C
 - Operating RH (non condensing) 10-80%
 - Non Operating RH (non condensing) 0-90%
 - **Shipping Weight**
 - < 8.0 lbs. (3.6kg) (Depending on configuration)
 - **Warranty**
 - 1 Year limited Warranty, Standard
 - Extended Warranty available, contact Stealth for more info.

Note: Specifications are subject to change without notice.
All other trademarks and copyrights are the property of their respective owners.