

**Features:**

- 6.5" OPEN FRAME LCD MONITOR
- Small Size 6.5" TFT LCD Monitor
- Very Bright 800 NITS
- Open Frame design for easy mounting
- 12VDC Operation ideal for Mobile
- True VGA, 640 x 480 resolution
- Touch Screen Operation (optional)
- Compatible with standard video cards
- No Drivers required
- Also available in Panel Mount Design



Rear View



Connectors View

**SV-650-OEM - Pricelist**

**6.5" OEM/Open-Frame LCD Monitor**

The StealthVU 6.5" Flat Panel Monitor is extremely compact and ideal for situations where conventional sized monitors won't fit into tight spaces. This mini monitor is an ideal companion of the newly released littlePCs with its small size form factor being able to fit into space challenged applications. Also operating from 12 VDC allows it to be easily deployed in mobile and field applications. Stealth Industrial LCD monitors are ideal for Operator Interface, Machine Control, Plant Floor or any application that requires superior image quality in a thin, low powered industrial package. Stealth provides wide ranges of industry proven products designed for continuous 24-hour operation and yet are priced to meet your budget!

**SV-650-OEM Specifications**

Screen Size	6.5" (Diagonal)
Aspect Ratio	4:3
Native Resolution	640 x 480

Horizontal Frequency	31.5 kHz ~ 80 kHz
Vertical Frequency	60 Hz
Pixel Pitch	0.207mm x 0.207mm
Response Time	15ms (Rise time), 10ms (Decay time) typical
Type	LCD c/w LED Backlighting
Viewable Image Size	Horizontal: 5.21" / 132.48 mm Vertical: 3.91" / 99.36 mm
Viewing Angle	160° / 140° (H / V) - <i>(Viewing angle of LCD panel sans touch/AR glass)</i>
Contrast Ratio	600:1 (typical)
Luminance (Brightness)	800 cd/m2 typical at center (800 Nits)
Connector Type	Standard: Analog 15 Pin D-Sub
Video Input Connectors	Analog (VGA / HD-15), DVI Compliant Digital HDCP (DVI-D)
Display Color	16.2 Million
Power Input	12V DC input, comes with external AC adapter, Input: 100-240V AC, 1.6A, 50/60 Hz
Control Buttons (Rear mounted)	Power, Up, Down, Menu, Auto
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Operating Temperature	-30 to 80C (-22 to 176 F) Humidity 5% to 95%, non-condensing
Storage Temperature	-30 to 80C (-22 to 176 F) Humidity 5% to 95%, non-condensing
Environmental	OEM/Open-Frame chassis - not rated
Panel Finish	N/A - Open-Frame
Weight	Unit only: 1.65 lbs (0.74Kg) Power supply only: 0.55 lbs (0.24Kg) Power cord only: 0.30 lbs (0.13Kg) VGA cable: 0.35 lbs (0.15Kg)

Shipping weight complete: 3.5 lbs (1.58Kg)

Available Open Frame (OEM) Models:

**SV-650-OEM**

- *No protective glass, LCD directly exposed*

**SV-650-OEM-RT-SERIAL**

- *Resistive Touch with Serial/DB9 Interface*

**SV-650-OEM-RT-USB**

- *Resistive Touch with USB Interface*

**SV-650-OEM-CT-SERIAL**

- *Capacitive Touch with Serial/DB9 Interface*

**SV-650-OEM-CT-USB**

- *Capacitive Touch Screen with USB interface*

Dimensions

**OEM Chassis:**

7.25"(W) x 6.02"(H) x 1.81"(D)

184mm x 194.9mm x 46mm

Additional Options

- ODM/OEM to meet exact needs, call to discuss your needs

Product Bundle

Bundle with a Stealth LittlePC or Panelmount Computer and Save

- *see pricelist links above for more details*

Warranty

1 Year Parts & Labor

*NOTE: Specifications subject to change without notice.*