



(shown with optional bench/desktop stand,
 click on images for larger pictures)

Features:

- **19" Rugged Metal Enclosed Industrial LCD Monitor**
- NEMA 4, IP65 - Sealed front panel
- Resistive Touch Screen
- Versatile VESA Mounting Options
- 19.0" Active Display Area
- Wide Viewing Angles, 170° (H) / 160° (V)
- Ideal for use in industrial and commercial environments
- 2 Year Warranty
- **Now with integrated Little PC option**
- Other sizes & options available.
Minimum quantities may apply.

TT-1900 - Pricelist

Model: TT-1900 - TuffTouch
 Metal Encapsulated Industrial Grade LCD Monitors

Finally a Rugged versatile Touch Screen LCD Monitor designed to stand-up to the rigors of industry. Stealth's TuffTouch LCD delivers performance and reliability that is ideally suited for industrial and commercial environments. TuffTouch is available with resistive touch screen option and includes a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Available with built-in Little PC. Our powerful small computers are integrated into the rear bracket of the TuffTouch LCD. In less than 1 minute Stealth's Small PC is installed with the easy-connect rear bracket. A simple and convenient way to upgrade service and install your application.

TT-1900 Specifications


Screen Size	19.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)

Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.294mm x 0.294mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input	VGA / HD15 and DVI-D
Viewing Angle	170° (H) / 160° (V) - <i>(Viewing angle of LCD panel sans touch/AR glass)</i>
Contrast Ratio	1000:1 (typical) SmartContrast: 20,000,000:1
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 14.81" / 376.32 mm Vertical: 11.85" / 301.06 mm
Video Input Connectors	Analog (VGA / HD-15), DVI Compliant Digital HDCP (DVI-D)
Sync Signal	Separate Sync, Sync on Green, (Positive/Negative)
Operating Temperature	0 - 40C (32 to 104 F) Humidity 20% ~ 80%, non-condensing Altitude Sea Level to 12,000 ft
Storage Temperature	-20C - 60C (-4 to 140 F) Humidity 20% to 80%, non-condensing Altitude Sea Level to 40,000 ft.
Input	AC Input: 100-240 V ~ 50/60 Hz, 0.7A @ 100-120VAC, 0.36A @ 220-240VAC
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental	NEMA 4 / IP65 Front Panel protection against windblown dust and rain, splashing water, and hose-directed water

Panel Finish / Enclosure	<ul style="list-style-type: none"> - Black Baked Enamel - Aluminum Alloy - 100mm VESA Rear Mount
Unit Weight	Unit 14 lbs (6.36 Kgs)

Available Models:	TT-1900-RT
- NEMA 4 / 4X sealed when properly installed	- <i>Resistive Touch with USB & Serial/DB9 Interfaces</i>

Dimensions	<p>Standard Config: 18.45" x 14.56" x 2.68" 468.63mm x 369.82mm x 68.07mm</p> <p>With Optional Mounting Bracket for LittlePC: 18.45" x 14.56" x 5.04" 468.63mm x 369.82mm x 128.14mm</p>
------------	--

LCD Mount Options	 <div style="display: flex; justify-content: space-around; text-align: center;"> <div>Ceiling Mount</div> <div>Wall Mount</div> <div>Fixed Mount</div> <div>Wall Mount</div> <div>LittlePC Mounted</div> </div>
-------------------	--

For more information and pricing on mounts please contact us.

Additional Options	<ul style="list-style-type: none"> - Various VESA Mount Brackets - Little PC Rear Mount Option - Other sizes & options available. <p><i>Minimum quantities may apply.</i></p>
--------------------	--

Included Accessories	<ul style="list-style-type: none"> - AC Power Cord - VGA Cable - Touch Screen Driver CD
----------------------	--

Product Bundle	<p>Bundle with a Stealth LittlePC or Panelmount Computer and Save</p> <p>- <i>see pricelist links above for more details</i></p>
----------------	--

Warranty	2 Year Parts & Labor
----------	----------------------

NOTE: Specifications subject to change without notice.