

Datasheet

Models: 1330-HULA-PM (PS/2 and USB)

(Panelmount NEMA 4, 4X, 12, IP56 Pointing Device)

The Stealth Computer Model 1330-HULA-PM is an environmentally sealed, industrial grade pointing device that combines the functionality of a mouse and the flexibility of a joystick in one convenient, small-footprint package.

The completely sealed, NEMA 4X, IP56 design is constructed from solid stainless steel and withstands spills, washdowns, contaminants, and the general rigors of an industrial environment. Ideal for kiosks, control panels, machines, Instrumentation or other applications.

Product Photo

Pointing Device Features



NEMA 4, 4X, IP56, Stainless Steel

- Rugged Stainless Steel Panel Mount front bezel
- Two-button Mouse
- Sensor Moves on 10 Degree Tilt for 360 Degree Movement
- 10 Million cycles expected life
- Ideal for Kiosk Applications
- Includes 10' Straight PS/2 or USB Cable
- Dimensions: 4.33"W x 2.25"H x 1.0"D

(click on image for a larger picture)

Technical Information

Ordering Information

Technical Specifications

Industrial Approvals

Nema 4, 4X, IP56 UL/ULc 60950, CE, FCC Class 15, Part B

Key Switch

Material: Industrial Silicone Rubber Life: Greater than 10 million cycles

Travel: 0.060" (1.5mm) Actuation Force: 5oz (130g)

Vibration

Power Special Density: 0.04g/Hz Frequency Range: 20Hz-2kHz Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 4.33" x 2.25" x 1.0" 109.9mm x 57.2mm x 25.4mm Feedback: Tactile with mechanical snap

Power

PS/2: 35mA @ 5V (from mouse Port) USB: 35mA @5V (from USB port)

Temperature Range

Storage: -40C to +90C (-40F to +194F) Operating: -40C to +70C (-40F to

+158F)

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Flammability

Printed Circuit Board: 94 VO Silicone Overlay: 94 HB Interface Cable: 94 VO Cable

Length: 10 feet (3.94 meters)

Design: 10' Straight PS/2 or USB Cable

Compatibility

Compatible with all Windows Operating Systems

Warranty:

1 Year Limited Warranty

Model Numbers

1330-HULA-PM-USB with USB Cable 1330-HULA-PM-PS/2 with PS/2 Cable

NOTE: Specifications subject to change without notice.