

Datasheet

Models: 5000-PMU (PS/2 and USB)

(NEMA 4, 4X, 12 panelmount keyboard, w/ Built-in Mouse)

The Stealth Computer rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. They meet NEMA 4, 4X specifications which enables them to survive in the roughest of conditions.

Product Photo



(click on image for a larger picture)

Keyboard Features

- NEMA 4, 4X, 12,
- ABS Polycarbonate Frame with 8-32 Mounting Studs
- 116 Keys, 24 Function Keys, WIN KEY
- Built-in 3 button HULA Pointing Device
- 10 Million cycles expected life
- Includes 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable
- Dimensions: 15.39"W x 7.06"D x 0.62"H

Ordering Information

Technical Information

Technical Specifications

- **Industrial Approvals**
Nema 4, 4X
UL/ULc 60950, CE, FCC Class 15, Part B
- **Key Switch**
Material: Industrial Silicone Rubber
Life: Greater than 10 million cycles
Travel: 0.060" (1.5mm)
Actuation Force: 5oz (130g)
Feedback: Tactile with mechanical snap
- **Power**
Keyboard: 5V@10ma (from CPU Port)
Hula: 5V@10ma (from mouse conn.)
- **Vibration**
Power Special Density: 0.04g/Hz
Frequency Range: 20Hz-2kHz
Duration of Test per Axis: 3 hours
- **Dimensions**
(W-D-H) 15.39" x 7.06" x 0.62"
390.9mm x 179.3mm x 15.7mm
CUTPIT: 13.36" x 5.03"
- **Cable**
Length: 10 feet (3.05 meters)
Design: Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable
- **Compatibility**
PS/2 & USB Keyboard/HULA:

port)

Compatible with all Windows Operating Systems

- **Temperature Range**
-40F to +194F (-40C to +90C)
- **Humidity**
100%
- **Shock**
3x11 ms pulses of 50g on each of 3 axes
- **Flammability**
Printed Circuit Board: 94 VO
Silicone Overlay: 94 HB
Interface Cable: 94 VO
- **Warranty:**
1 Year Limited Warranty
- **Model Numbers**
5000-PMU-PS/2 (PS/2 Interface)
5000-PMU-USB (USB Interface)

NOTE: Specifications subject to change without notice.