



**Model: FR-1501-17 -
Datasheet**

Features:

- **17" Slim 1U Rack LCD Monitor**
- Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
- Folds down to 1U, 1.75" high
- LCD Stays Open inside a Rack Cabinet
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
- Built-in lockable Slide Rails
- Optional: DC Power, Screen Sizes, Video Inputs, Touchscreen



Front View
with open LCD



Rear View
and open

**FR-1501-17 -
Pricelist**

17" LCD Monitor 1U Rack Drawer

Optimize Rack Space with a Slim 1U LCD Monitor in a Drawer

Stealth FlatRack LCD monitors have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

The Stealth ultra-thin LCD monitor can operate in its open state even with the rack cabinet doors closed. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

Stealth.Com is an ISO 9001 manufacturer with over two decades of delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584) or International 905-264-9000.

FR-1501-17 Specifications

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	1.3ms Typical
Viewable Image Size	Horizontal: 13.3" / 338 mm Vertical: 10.6" / 270 mm
Video Input	VGA / HD15 (Standard) DVI-D (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Built-in Controls for Brightness, Size, Contrast, H-V Position, Frequency, etc.
Inputs	Video: ANALOG: 0.7Vp-p
Power (VAC/VDC)	Internal 100~240VAC, 50/60Hz Power Supply
Power Consumption	Max. 48 Watts, Standby 5 Watts
Security	Latching front panel w/ 2-point lock
Operating Temperature	0 - 50C (32 to 122 F)
Storage Temperature	-5 - 60C (-23 to 140 F)
Humidity	5~90%, non-condensing
Shock	10G acceleration (11ms duration)
Vibration	5~500Hz 1G RMS random vibration
Color	Black (standard)

Unit Weight	Unit 26 lbs.(12.0 kgs.)
-------------	-------------------------

Available Models:	FR-1501-17 - <i>Standard Model</i>
-------------------	--

Dimensions	19.0"(W) x 1.75"(H) x 21.7"(D) (482.6 x 44.0 x 551.18 mm)
------------	--

Additional Options	- Resistive/Capacitive Touchscreen - 12/24/48VDC Power supply - DVI-D, BNC, S-Video, RCA Inputs
--------------------	---

Available Documents	
---------------------	--

Pricelists:



Product Bundle	Bundle with a Stealth Rackmount Computer and Save - <i>see pricelist links above for more details</i>
----------------	--

Warranty	2 Year Parts & Labor
----------	----------------------

NOTE: Specifications subject to change without notice.