

## Datasheet

### Models: OEM-HULA (PS/2 and USB)

(OEM/Open-Frame NEMA 4, 4X, 12 Pointing Device)

The Stealth Computer model OEM-HULA is the OEM version of the Hula industrial pointing device offers the same functionality as the enclosed Hula. It has the same low profile design with no protruding parts.

#### Product Photo



(click on image for a larger picture)

#### Pointing Device Features

- NEMA 4, 4X, 12
- ABS-Polycarbonate Sealed Plastic Case
- Right and Left Click, Plus Programmable Button Sensor Moves on 10 Degree Tilt for 360 Degree Movement
- 10 Million cycles expected life
- Ideal for Kiosk Applications
- Includes 10' cable w/ 5-pin DIN, 9-pin serial connectors, PS/2 or USB cables
- Dimensions: 3.5"W x 3.5"D x 0.5"H

#### Technical Information

#### Ordering Information

#### Technical Specifications

- **Industrial Approvals**  
Nema 4, 4X  
UL/ULc 60950, CE, FCC Class 15, Part B
- **Key Switch**  
Material: Industrial Silicone Rubber  
Life: Greater than 10 million cycles  
Travel: 0.060" (1.5mm)  
Actuation Force: 5oz (130g)
- **Vibration**  
Power Spectral Density: 0.04g/Hz  
Frequency Range: 20Hz-2kHz  
Duration of Test per Axis: 3 hours
- **Dimensions**  
(W-H-D) 3.5" x 3.5" x 0.5"  
88.9mm x 88.9mm x 12.7mm
- **Cable**  
Length: 10 feet (3.94 meters)  
Design: "Y" PS2 pr AT/serial Cable,

Feedback: Tactile with mechanical snap

- **Power**  
5V@10ma (from CPU Port)
- **Temperature Range**  
-40F to +194F (-40C to +90C)
- **Humidity**  
100%
- **Shock**  
3x11 ms pulses of 50g on each of 3 axes
- **Flammability**  
Printed Circuit Board: 94 VO  
Silicone Overlay: 94 HB  
Interface Cable: 94 VO

or Single Cable USB

- **Compatibility**  
Compatible with all Windows Operating Systems
- **Warranty:**  
1 Year Limited Warranty
- **Model Numbers**  
OEM-HULA-USB (USB Interface)  
OEM-HULA-PS/2 (PS/2 Interface)

*NOTE: Specifications subject to change without notice.*